

PRODUCT-DETAILS

CA26

CA26 Comp.DB 2PW 6R empty w.door



General Information

| | |
|-----------------------|----------------------------------|
| Extended Product Type | CA26 |
| Product ID | 2CPX052151R9999 |
| EAN | 4011617521518 |
| Catalog Description | CA26 Comp.DB 2PW 6R empty w.door |

Long Description

compact distribution boards, empty cabinet, for the internal use, with Door, class of protection II (double insulated), in combination with earthing set (accessory) we can achieve protection class 1, degree of protection IP44, applicable standards: EN 61439-1, EN 61439-3, Rated operational voltage 400V AC 50/60 Hz, rated current 125 A, powder-coated, in RAL 9016, enclosure out of sheet steel, metal door, door out of sheet steel, in RAL 9016, with Standard closure, door opening angle 120 degree, door hinge right or left, cable entry on top via membrane flange mounted, on bottom via flange opening pre-punched, dimensions in mm (H x W x D): 950 x 550 x 160, Grid unit 6 GU, panel width 2, Space units 144, without N/PE Quick-terminal, cable fastening rail integrated, pre-assembled for installation of modules and CombiLine Modules

Ordering

| | |
|------------------------|---------------|
| EAN | 4011617521518 |
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85381000 |

Dimensions

| | |
|--------------------|--------|
| Product Net Width | 550 mm |
| Product Net Height | 950 mm |

| | |
|----------------------------|-----------|
| Product Net Depth / Length | 160 mm |
| Product Net Weight | 13.872 kg |

Container Information

| | |
|--------------------------------|------------------------|
| Package Level 1 Units | pack 1 piece |
| Package Level 1 Width | 556.000 mm |
| Package Level 1 Height | 952.000 mm |
| Package Level 1 Depth / Length | 165.000 mm |
| Package Level 1 Gross Weight | 14.427 kg |
| Package Level 1 EAN | 4011617521518 |
| Package Level 2 Units | pallet (lift) 12 piece |
| Package Level 2 Width | 800.000 mm |
| Package Level 2 Height | 1800.000 mm |
| Package Level 2 Depth / Length | 1200.000 mm |

Additional Information

| | |
|---------------------------|--|
| Color | traffic white |
| Configuration Type | pre-assembled for installation of modules and CombiLine Modules |
| Cover Plate Type | Door |
| Degree of Protection | IP44 |
| DIN Place Units | 144 |
| Enclosure Type | compact distribution boards |
| Field Width | 2 |
| Housing Material | Steel |
| Interior Depth | 135.1 mm |
| Mounting Type | Surface-mounted |
| Number of Rows | 6 |
| Operational Voltage | 400 V |
| Power Loss | $\Delta t = 20K$ 69.3 W $\Delta t = 25K$ 91.5 W $\Delta t = 30K$ 114.8 W |
| Product Main Type | ComfortLine Compact CA |
| Product Name | CA26 Comp.DB 2PW 6R empty w.door |
| Protection Class | Isolated |
| Rated Current (I_n) | 125 A |
| Rated Operational Voltage | Maximum 400 V |
| Standards | DIN EN 61439-3 |
| Terminal Type | Quick-Terminal |

Certificates and Declarations (Document Number)

| | |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 9AKK107680A4771 |
| Instructions and Manuals | 2CPC133150M5601 |

Classifications

ETIM 7

EC000214 - Small distribution board

Object Classification Code

U

WEEE Category

Product Not in WEEE Scope

Categories

Low Voltage Products and Systems → Enclosures → Sub Distribution Boards → Compact Distribution Boards - Modules Assembled → ComfortLine Compact CA

