

PRODUCT-DETAILS

3125MVS11WH

Switched interlocked socket-outlet, vertical,
Heavy Duty, 11h, 125A, IP67, 3P+E



General Information

| | |
|-----------------------|--|
| Extended Product Type | 3125MVS11WH |
| Product ID | 2CMA162745R1000 |
| EAN | 7392696627450 |
| Catalog Description | Switched interlocked socket-outlet, vertical, Heavy Duty, 11h, 125A, IP67, 3P+E |
| Long Description | Switched Interlocked Socket Outlet, vertical, Heavy Duty, earthing sleeve position 11h, rated current 125A, IP67 watertight, 3-poles+earth |

Ordering

| | |
|------------------------|---------------------|
| E-Number (Sweden) | 2416969 |
| E-Number (Finland) | 2416969 |
| E-Number (Norway) | 2416969 |
| EAN | 7392696627450 |
| Country of Origin | Czech Republic (CZ) |
| Minimum Order Quantity | 1 piece |

Dimensions

| | |
|--------------------|--------|
| Product Net Width | 175 mm |
| Product Net Height | 241 mm |

| | |
|---------------------|-----------------|
| Product Net Weight | 4.3 kg |
| Mechanical Drawings | 9AKK107991A3935 |

Container Information

| | |
|--------------------------------|------------------------|
| Package Level 1 Width | 180 mm |
| Package Level 1 Depth / Length | 490 mm |
| Package Level 1 Height | 260 mm |
| Package Level 1 Gross Weight | 4.3 kg |
| Package Level 1 EAN | 7392696627450 |
| Package Level 1 Units | box 1 piece |
| Package Level 2 Width | 800 mm |
| Package Level 2 Depth / Length | 1200 mm |
| Package Level 2 Height | 900 mm |
| Package Level 2 Gross Weight | 140.4 kg |
| Package Level 2 EAN | 7392696068208 |
| Package Level 2 Units | pallet (lift) 28 piece |

Environmental

| | |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

Certificates and Declarations (Document Number)

| | |
|--------------------------------|-----------------|
| CB Certificate | 2CHC660160X0201 |
| Declaration of Conformity - CE | 2CMC700005D0001 |
| Environmental Information | 2CMC000057M0000 |
| RoHS Information | 2CMC700005D0001 |
| SEMKO Certificate | 1506655 |
| REACH Declaration | 2CMC700005D0001 |

Additional Information

| | |
|------------------------|---|
| Additional Information | 3P+E |
| Ambient Temperature | -25 ... 40 °C |
| Cable Cross-Section | 16 ... 70 mm ² |
| Cable Diameter | 24 ... 48 mm |
| Cable Entry Position | Knock-out on Top and drill marks down |
| Cable Outlets Per Side | 1xØ40+1xØ50 mm on top and drill marks on bottom |
| Color | Red |
| Connection Type | Screw |
| Degree of Protection | IP67 IP69 |

| | |
|---------------------------------|--|
| Frequency (f) | 60 Hz |
| Function | Switched Interlocked Socket outlet, vertical, Heavy Duty |
| Housing Material | Thermoplastic (PBT) |
| Invoice Description | IND. P&S#3125MVS11WH |
| Mounting Holes | 378x145, 128x145 |
| Mounting Type | Vertical |
| Number of Auxiliary Contacts NO | 1 |
| Number of Poles | 4 |
| Order Multiple | 1 piece |
| Product Main Type | CMVS |
| Product Name | Industrial Switched Interlocked Socket Outlet |
| Protection Type | Switched Interlocked |
| Rated Current (I_n) | 125 A |
| Rated Voltage (U_r) | 440 ... 460 V |
| Recommended Screw Driver | PH2 |
| Standards | IEC 60309-1, -2, -4 |
| Suitable For | Switched Interlocked Socket Outlets, Vertical |
| Suitable for Product Class | IEC Industrial Plugs and Sockets |
| Instructions and Manuals | 2CMC000043M0001 |
| Installation Manual | 2CMC000043M0001 |
| RAL Number | RAL 7001 - Silver Grey |

Classifications

| | |
|--------|----------|
| eClass | 27440510 |
| UNSPSC | 39120000 |

Technical

| | |
|-------------------|------------------|
| Wire Size | 3 ... 1 AWG |
| Tightening Torque | WireClamp5.6 N·m |

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Critical & Safe → Switched Interlocked Socket Outlets

