

PRODUCT-DETAILS

# CUCB-S4/250 400V-6h

## Ind. P&S#CUCB-S4/250 400V-6h



### General Information

Extended Product Type	CUCB-S4/250 400V-6h
Product ID	2CMA103556R1000
EAN	7392696035569
Catalog Description	Ind. P&S#CUCB-S4/250 400V-6h
Long Description	Connector Unit with Circuit Breaker, yellow painted steel enclosure, 1200X800X379, CUCB-S4/250 400V-6h, 3P+E

### Ordering

EAN	7392696035569
Country of Origin	Switzerland (CH)
Minimum Order Quantity	1 piece

### Dimensions

Product Net Width	360 mm
Product Net Height	360 mm
Product Net Weight	45.6 kg

---

**Container Information**


---

Package Level 1 Width	883 mm
Package Level 1 Depth / Length	883 mm
Package Level 1 Height	362 mm
Package Level 1 Gross Weight	45.6 kg
Package Level 1 EAN	7392696035569
Package Level 1 Units	box 1 piece

---

**Certificates and Declarations (Document Number)**


---

Declaration of Conformity - CE	NoDecNee
Environmental Information	2CMC000074M0000

---

**Additional Information**


---

Additional Information	3P+E
Ambient Temperature	-40 ... 70 °C
Cable Diameter	20 ... 65 mm
Color	Red
Connection Type	Screw Clamp
Degree of Protection	IP55
Frequency (f)	50 Hz 60 Hz
Function	Connector Unit with Circuit Breaker
Housing Material	Steel
Invoice Description	Ind. P&S#CUCB-S4/250 400V-6h
Mounting Holes	310x580
Number of Poles	4
Order Multiple	1 piece
Product Main Type	CUCB
Product Name	Connector Unit with Circuit Breaker
Protection Type	Mini circuit breaker
Rated Current ( $I_n$ )	250 A
Rated Voltage ( $U_r$ )	380 ... 415 V
Standards	IEC 60309-1, -2
Sub-Function	B-line
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 1004 - Golden Yellow

---

**Classifications**


---

eClass	27440508
UNSPSC	39120000

---

---

## Categories

---

Low Voltage Products and Systems → Industrial Plugs and Sockets → High Current Connectors >125A

