Product data sheet Characteristics

XBKH70000004M

hour counter - mechanical 7 digit display - 24 V AC



| Main | |
|---------------------------|-------------------|
| Range of product | Zelio Count |
| Product or component type | Hour counter |
| Display type | Mechanical |
| Size | 48 x 48 mm |
| Display digits | 7 digit(s) |
| Reset | Without |
| Technology type | Electromechanical |

Complementary

| Complementary | | |
|---------------------------|--------------------------------|--|
| [Us] rated supply voltage | 24 V AC (Us +/- 10 %) at 50 Hz | |
| Power consumption | 0.08 VA | |
| Backup time | Permanent | |
| Counting mode | Adding 1/100 of an hour | |
| Time range | 099 999.99 h | |
| Input function | Enable | |
| Input type | Contact | |
| Mounting mode | Flush-mounted | |
| Mounting support | Panel mounting | |
| Fixing mode | By self-locking clamp | |
| Connections - terminals | Screw terminal block | |
| Height | 48 mm | |
| Product weight | 0.06 kg | |
| Width | 48 mm | |
| Character size | 5 mm | |

Environment


| EN 50081-2 | |
|--|--|
| EN 50082-2 | |
| VDE 0435 | |
| UR | |
| IP65 conforming to EN/IEC 60529 | |
| -1050 °C | |
| -2570 °C | |
| 3 gn (f = 10150 Hz) conforming to EN/IEC 60068-2-6 | |
| 30 gn for 11 ms conforming to EN/IEC 60068-2-27 | |
| Class II conforming to EN/IEC 60536 | |
| | EN 50082-2 VDE 0435 UR IP65 conforming to EN/IEC 60529 -1050 °C -2570 °C 3 gn (f = 10150 Hz) conforming to EN/IEC 60068-2-6 30 gn for 11 ms conforming to EN/IEC 60068-2-27 |

XBKH7000004M


Electromechanical and Electronic Totalizing Timers

Timers with Mechanical Display

XBKH7000000•M




Flush-Mounting



Timers with LCD Display

XBKH81000033E



Flush-Mounting

