

PRODUCT-DETAILS

OT200E12C

OT200E12C CHANGE-OVER SWITCH



General Information

| | |
|-----------------------|---|
| Extended Product Type | OT200E12C |
| Product ID | 1SCA022776R8600 |
| EAN | 6417019252933 |
| Catalog Description | OT200E12C CHANGE-OVER SWITCH |
| Long Description | Handle and shaft has to be ordered separately |

Ordering

| | |
|------------------------|--------------|
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85365080 |
| Country of Origin | Finland (FI) |

Popular Downloads

| | |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SCC303003C0201 |
| Instructions and Manuals | 1SCC303008M0203 |

Dimensions

| | |
|--------------------|--------|
| Product Net Width | 170 mm |
| Product Net Height | 150 mm |

| | |
|----------------------------|-------------------|
| Product Net Depth / Length | 160 mm |
| Product Net Weight | 2.9 kg 6.39 lb |

Technical

| | |
|--|--|
| Rated Operational Current AC-21A (I_e) | (380 ... 415 V) 200 A (500 V) 200 A (690 V) 200 A |
| Rated Operational Current AC-22A (I_e) | (380 ... 415 V) 200 A (500 V) 200 A (690 V) 200 A |
| Rated Operational Current AC-23A (I_e) | (380 ... 415 V) 200 A (500 V) 200 A (690 V) 200 A |
| Rated Operational Current AC-31B (I_e) | (380 ... 415 V) 200 A |
| Rated Operational Current AC-33B (I_e) | (380 ... 415 V) 200 A |
| Rated Operational Power AC-23A (P_e) | (380 ... 415 V) 110 kW (500 V) 132 kW (690 V) 200 kW |
| Conventional Free-air Thermal Current (I_{th}) | q = 40 °C 200 A |
| Conventional Thermal Current (I_{the}) | Fully Enclosed 200 A |
| Rated Impulse Withstand Voltage (U_{imp}) | 12 kV |
| Rated Insulation Voltage (U_i) | 1000 V |
| Rated Operational Voltage | 1000 V |
| Rated Short-time Withstand Current (I_{cw}) | for 1 s 8 kiloampere rms |
| Power Loss | 4 W |
| Pollution Degree | 3 |
| Handle Color | Black |
| Handle Type | Handle and shaft not included |
| Switches Operating Mechanism | Mechanism Between the Poles 12 (Between the Poles) |
| Distance Between Phases | Standard |
| Position of Line Terminals | Top In - Bottom Out, Bottom In - Top Out |
| Operating Mode | Front operated |
| Mounting Type | Base mounting |
| Number of Poles | 3 |
| Degree of Protection | Front IP20 |
| Transition Type | Open |

Environmental

| | |
|---------------------------|-----------------|
| Environmental Information | 1SCC303050D0201 |
|---------------------------|-----------------|

Certificates and Declarations (Document Number)

| | |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 1SCC303002D0202 |
|--------------------------------|-----------------|

| | |
|---------------------------|-----------------|
| Environmental Information | 1SCC303050D0201 |
| Instructions and Manuals | 1SCC303008M0203 |

Container Information

| | |
|--------------------------------|--------------------|
| Package Level 1 Units | 1 piece |
| Package Level 1 Width | 186 mm 7.32 in |
| Package Level 1 Depth / Length | 300 mm 11.81 in |
| Package Level 1 Height | 185 mm 7.28 in |
| Package Level 1 Gross Weight | 3.2 kg 7.05 lb |
| Package Level 1 EAN | 6417019252933 |

Classifications

| | |
|----------------------------|--|
| Object Classification Code | Q |
| ETIM 5 | EC000216 - Switch disconnecter |
| ETIM 6 | EC000216 - Switch disconnecter |
| ETIM 7 | EC000216 - Switch disconnecter |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |

Categories

Low Voltage Products and Systems → Switches → Change-over and Transfer Switches → Manual Change-over Switches

