

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3205B

SIMOTICS SD - 200 L - IM B3 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project
Remarks		

Electrical data

Safe Area

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	η ³⁾			$\cos\phi$ ³⁾			I_A/I_N I_i/I_N	M_A/M_N T_i/T_N	M_k/M_N T_B/T_N	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4				
400	Δ	50	30.00	-/-	55.00	1470	195.0	93.6	94.0	93.7	0.84	0.80	0.71	7.3	2.6	3.1	IE3
690	Y	50	30.00	-/-	32.00	1470	195.0	93.6	94.0	93.7	0.84	0.80	0.71	7.3	2.6	3.1	IE3
460	Δ	60	34.50	-/-	55.00	1770	186.0	93.0	93.3	92.9	0.85	0.81	0.73	7.3	2.4	3.0	IE2
460	Δ	60	30.00	-/-	48.00	1778	161.0	94.1	94.2	93.6	0.83	0.79	0.70	8.8	2.6	3.5	IE3
IM B3 / IM 1001		FS 200 L		IP55		IEC/EN 60034		IEC, DIN, ISO, VDE, EN									
Environmental conditions : -20 °C - +40 °C / 1,000 m								Locked rotor time (hot / cold) : 28.6 s 43.8 s									

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	75 / 79 dB(A) ²⁾	75 / 79 dB(A) ²⁾	Vibration severity grade	A
Moment of inertia	0.2400 kg m ²		Insulation	155(F) to 130(B)
Bearing DE NDE	6212 Z C3	6212 Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} , F _{Rad} min 50 60Hz ¹⁾ for coupling operation	40000 h	32000 h	Frame material	cast iron
Lubricants	Unirex N3		Net weight of the motor (IM B3)	240 kg
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	(B) 3 PTC thermistors - for tripping (2 terminals)
Condensate drainage holes	Yes (standard)		Method of cooling	IC416 - separately ventilated, surface cooled
External earthing terminal	Yes (standard)			

Terminal box

Terminal box position	right	Max. cross-sectional area	25 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	27 mm - 35 mm
Type of terminal box	TB1 L01	Cable entry	2xM50x1,5-2xM20x1,5
Contact screw thread	M6	Cable gland	4 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
 M_k/M_N = locked rotor torque / torque nominal
 M_k/M_N = break down torque / nominal torque
¹⁾ L10mh according to DIN ISO 281 10/2010
²⁾ at rated power / at full load
³⁾ Value is valid only for DOL operation with motor design IC411

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	<i>Technical data are subject to change! There may be discrepancies between calculated and rating plate values.</i>			
SIEMENS	document type datasheet	document status released		customer			
	title 1LE1503-2AB53-4AB5-Z B02+F70+G11+Y82	document number					
© Siemens AG 2021	rev. 01	creation date 2021-11-15 17:05	language en	Page 1/2			

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3205B

SIMOTICS SD - 200 L - IM B3 - 4p

Special design

B02	Acceptance test certificate 3.1 acc. to EN 10204	G11	Rotary pulse encoder Sendix 5020 (HTL)
F70	Mounting of separately driven fan	Y82	Auxiliary name plate with customer data

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	<i>Technical data are subject to change! There may be discrepancies between calculated and rating plate values.</i>
-------------------------------	---------------------	-------------------------------	-------------	---

SIEMENS	document type datasheet	document status released	customer	
	title 1LE1503-2AB53-4AB5-Z B02+F70+G11+Y82	document number	rev. 01	creation date 2021-11-15 17:05
© Siemens AG 2021				Page 2/2