

FAST LOCK-OUT RELAY 8 CHANGE OVER CONTACTS OPERATING TIME 10MS AUXILIARY VOLTAGE: 24/30V DC WITH RESET PUSHBUTTON WITHOUT SOCKET



Figure similar

General technical data	
type of voltage	DC
continuous current	10 A
switching behavior	bistable
design of the switching function / positively driven	Yes
response time	10 ms
Product details	
product component / LED	No
Product Functions	
manual RESET	Yes
Supply voltage	
supply voltage / at DC / rated value	24 V
Inputs / Outputs	
number of NC contacts	0
number of NO contacts	0
number of CO contacts	8
switching capacity active power / at DC / maximum	4 400 W
switching capacity active power / at DC / maximum / note	at 110V DC
Mechanical Design	
width	90 mm
height	50 mm
depth	112 mm
design of the snap-on socket base	without
Degree of protection / protection class	
protection class IP / on the front	IP40
protection class IP / rear side	IP10
Environmental conditions	
ambient temperature / during operation	-40 ... +70 °C
Further information	

**Information- and Downloadcenter (catalogues, leaflets,...)**

<http://www.siemens.com/energy-automation>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=7PA2211-0>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/7PA2211-0>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=7PA2211-0](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=7PA2211-0)

**Tender specifications**

<http://www.siemens.com/specifications>

