

## Data sheet for SIMOTICS S-1FL6

MLFB-Ordering data

1FL6024-2AF21-1AG1



Figure similar

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Engineering data		Mechanical data			
Rated speed	3000 rpm	Motor type	Low Inertia		
Rated torque (100 K)	0.32 Nm	Motor type	Permanent-magnet synchronous motor		
Rated current	1.2 A	Shaft height	20		
Rated power	0.10 kW / 0.14 hp	Encoder system	Incremental encoder TTL, 2500 S/R (13 bit)		
Max. speed	5000 rpm	Cooling	Natural cooling		
Maximum torque	0.96 Nm	Shaft end	Plain shaft		
Max. current	3.6 A	Radial runout tolerance	Class N		
Static torque	0.32 Nm	Vibration severity grade	Grade A		
Moment of inertia	0.052 kgcm <sup>2</sup>	Degree of protection	IP65		
<b>Physical constants</b>		Design acc. to Code I	IM B5 (IM V1, IM V3)		
		Torque constant	0.29 Nm/A	Connection type	Cable outlet
		Thermal class	B (130 °C)		
Net weight	0.60 kg				
<b>Ambient conditions</b>					
<b>Ambient temperature</b>					
Operation	0 ... 40 °C				
<b>Relative humidity</b>					
Max. operation	90 % RH maximum (no condensation at 30 °C)				
<b>Standards</b>					
Compliance with standards	CE, EAC				