

Contactor assembly for reversing Size 00, AC-3, 4 kW/400 V 24 VDC DC operation DC operation !!! Phased-out product !!! Successor is SIRIUS 3RA23

product function	Reversing contactor
protection class IP on the front	IP00
reference code acc. to IEC 81346-2	Q
Substance Prohibitance (Date)	01.07.2006
ambient temperature during operation	-25 ... +55 °C
operational current at AC-3 at 400 V rated value	9 A
operating power at AC-3 at 400 V rated value	4 kW
type of voltage of the control supply voltage	DC
control supply voltage 1	
• at DC rated value	24 V
number of NC contacts for auxiliary contacts per direction of rotation	0
number of NO contacts for auxiliary contacts per direction of rotation	1
fastening method	screw fixing
type of electrical connection for main current circuit	screw-type terminals

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3TD2003-1BB4>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3TD2003-1BB4>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3TD2003-1BB4>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3TD2003-1BB4&lang=en

Characteristic: Tripping characteristics, I^t, Let-through current

<https://support.industry.siemens.com/cs/ww/en/ps/3TD2003-1BB4/char>

Further characteristics (e.g. electrical endurance, switching frequency)

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3TD2003-1BB4&objecttype=14&gridview=view1>

last modified:

12/23/2020 