

SITRANS LR250 Radar level transmitter: continuous, non-contact, 20 m (66 ft) range, for liquids and slurries. Process Connection and Antenna Material: 316L (1.4435 or 1.4404) stainless steel, PTFE emitter, FKM seal Process Connection Type: Threaded connections 316L: G 1-1/2" ((BSPP), EN ISO 228-1) (parallel thread) Communication/Output: 4-20mA HART, start-up at < 3.6mA . Enclosure/Cable inlet: Aluminum, 2 x M20 x 1.5 Antenna Version, Size/Extension: Antenna /Extension 316L: 1-1/2 inch Horn Approvals: Increased Safety: IECEx/ATEX II 1/2 GD,1D, 2D Ex e mb ia IIC T4 Ga/Gb, Ex ia ta IIIC T100 C Da, INMETRO Ex e ia mb IIC T4 Ga/Gb, Ex ia ta IIIC T100 C Da, CE, RED, RCM Pressure Rating: Rating per pressure/temperature curves in instruction manual

## Further information

Industry Online Support (Manuals, Catalogs, Certificates, FAQ, ...)

<https://support.industry.siemens.com/cs/products?mf=ps&lc=en-WW>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com>

