

XAMWD04

empty elbowed control station - XAM-W -
aluminium alloy - 4 cut-outs - grey

Main

Range of product	Harmony XAM
Product or component type	Empty elbowed control station
Device short name	XAMW
Product destination	For Ø 22 mm control and signalling units
Number of cut-out	4 cut-outs
Colour of base of enclosure	Light grey RAL 7035
Colour of cover	Dark grey RAL 7016
Material	Aluminium alloy
Cable entry	Via opening in rear of enclosure
Product mounting	Flush mounting on vertical support
IP degree of protection	IP65 conforming to IEC 60529
Resistance to chemical agents	Good resistant to salts Good resistant to organic acids Good resistant to oils and petrol Good resistant to diluted mineral acids Good resistant to chloride and fluoride solvents Good resistant to alcohols Good resistant to acetone

Complementary

Product weight	0.725 kg
Flame retardance	VO conforming to UL 94 M3 conforming to CSTB

Environment

Protective treatment	TC TH
Ambient air temperature for storage	-40...70 °C
Ambient air temperature for operation	-25...70 °C
Class of protection against electric shock	Class I conforming to IEC 60536
Fire resistance	960 °C conforming to IEC 92 850 °C conforming to NF C 20-455
Standards	EN/IEC 60947-1 EN/IEC 60947-5-1 EN/IEC 60947-5-4

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.