



Main

Range	TeSys
Product or component type	Undervoltage trip
Device short name	GV7AS
Range compatibility	TeSys TeSys GV7

Complementary

[Uc] control circuit voltage	200...240 V AC 50/60 Hz
Control circuit voltage limits	0.85...1.1 Un
[Ui] rated insulation voltage	600 V AC conforming to CSA C22.2 No 14 control circuit 690 V AC conforming to IEC 60947-1 control circuit 600 V AC conforming to UL 508 control circuit
Threshold tripping voltage	0.35...0.7 Ue
Inrush power in VA	< 10 VA for AC network
Hold-in power consumption in VA	< 5 VA for AC network
Operating time	< 50 ms conforming to IEC 60947-1
On-load factor	100 %
Connections - terminals	Control circuit : screw clamp terminals 1 cable 1.5 mm ² - cable stiffness: solid Control circuit : screw clamp terminals 1 cable 1.5 mm ² - cable stiffness: flexible - without cable end Control circuit : screw clamp terminals 1 cable 1 mm ² - cable stiffness: flexible - with cable end
Tightening torque	Control circuit : 1.2 N.m - on screw clamp terminals
Product weight	0.11 kg
Quantity per set	Set of 10

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.