

Coupling relay - PSR-SPP- 24DC/FSP/2X1/1X2 - 2986957

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Safe coupling relay for SIL 3 high and low demand applications, coupled digital output signals to the I/O, 2 enabling current paths, 1 signal contact, module for safe state off applications, integrated test pulse filter, width: 17.5 mm, pluggable Push-in terminal block


The figure shows a version with a screw connection

Your advantages

- ✓ Narrow 17.5 mm housing
- ✓ Up to SIL 3 in accordance with IEC 61508
- ✓ Easy proof test according to IEC 61508 thanks to integrated signal contact
- ✓ Long service life thanks to filtering of controller test pulses
- ✓ Forcibly guided contacts according to EN 50205
- ✓ 2 enabling current paths
- ✓ Couples digital output signals from failsafe controllers to I/O devices (valves, etc.) for electrical isolation and power adaptation



Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 520928
GTIN	4046356520928
Weight per Piece (excluding packing)	200.000 g
Custom tariff number	85364900
Country of origin	Germany