



### Main

Range	TeSys
Device short name	LA1SK
Product or component type	Auxiliary contact block
Product compatibility	LC1SK
Auxiliary contacts operation	Instantaneous
Pole contact composition	1 NO + 1 NC
Connections - terminals	Screw clamp terminals 2 cable 0.35...1.5 mm <sup>2</sup> - cable stiffness: flexible - without cable end Screw clamp terminals 1 cable 0.35...6 mm <sup>2</sup> - cable stiffness: flexible - without cable end Screw clamp terminals 2 cable 0.35...2.5 mm <sup>2</sup> - cable stiffness: flexible - with cable end Screw clamp terminals 1 cable 0.5...6 mm <sup>2</sup> - cable stiffness: flexible - with cable end Screw clamp terminals 2 cable 1.5...4 mm <sup>2</sup> - cable stiffness: solid Screw clamp terminals 1 cable 1.5...6 mm <sup>2</sup> - cable stiffness: solid

### Complementary

Mounting location	Front side
[Ui] rated insulation voltage	690 V - conforming to CSA C22.2 No 14 690 V - conforming to VDE 0110 group C 690 V - conforming to BS 5424 690 V - conforming to IEC 60947
[Ue] rated operational voltage	690 V AC <= 400 Hz
[Ith] conventional free air thermal current	10 A at <= 55 °C
Associated fuse rating	VDE 0660 IEC 60947
Tightening torque	0.8 N.m - on screw clamp terminals
Width	27 mm
Product weight	0.022 kg

### Environment

Standards	BS 5424 IEC 60947 NF C 63-110 VDE 0660
Product certifications	CSA UL
IP degree of protection	IP2x
Protective treatment	TC conforming to IEC 60068
Ambient air temperature for operation	-20...50 °C
Ambient air temperature for storage	-50...70 °C
Operating altitude	2000 m without derating in temperature

### Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Compliant - since 0718 - <a href="#">Schneider Electric declaration of conformity</a>