

DESINA HYBRIDFIELDBUS

PUR 2x0.34 + 4x1,5 violet 10m

DESINA® ECOFAST® Male straight - female straight 6-pole, CU shielded

Further cable lengths on request.

Han-Brid ® a registered trademark of HARTING KGaA.


Plastic housings with good resistance against chemicals and oils.


The resistance to aggressive media should be individually tested for your application. Further details on request.

Link to Product

Illustration







CU CU

PIN 1: 24 V not switched PIN 2: 0 V corresponds to 1 PIN 3: 0 V corresponds to 4 PIN 4: 24 V switched

Product may differ from Image

_	
Form	
Form	33011
Technical Data	
Operating voltage	max. 24 V AC/DC
Operating current per contact	max. 10 A
Protection	IP67 inserted and tightened (EN 60529)
Locking of ports	Clip locking
General data	
Temperature range	-25+85 °C, depending on cable quality
Cables	
Cable number	964
No./diameter of wires	4× 1.5 + 2× 0.34 mm²
Wire isolation	PVC (bk num), (rd, gn)
Jacket Color	violet
Material (jacket)	PUR
Outer Ø	10.0 mm ±5%

The information in this brochure has been compiled with the utmost care.

Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 03/22



Bend radius (moving)	8× outer Ø	
Temperature range (fixed)	-30+70 °C	
Temperature range (mobile)	-40+60 °C	
Commercial data		
country of origin	DE	
customs tariff number	85444290	
EAN	4048879186780	
eClass	27279218	
Packaging unit	1	