

circuit breaker VL160L very high breaking capacity I<sub>cu</sub>=100kA, 415V AC 3-pole, line protection Electronic Trip Unit ETU10, I<sub>N</sub>=160A, rated current I<sub>R</sub>=64...160A, overload protection, I<sub>l</sub>=1.25 to 11xI<sub>N</sub>, short-circuit protection without auxiliary release Auxiliary/alarm switch mounting kit 2 AUX (1 NO+1 NC)+1 AS (1 NO)

Model	
type of the driving mechanism / motor drive	No
design of the overcurrent release	ETU10
General technical data	
number of poles	3
size of the circuit-breaker	3VL2
mechanical service life (switching cycles) / typical	20 000
electrical endurance (switching cycles) / typical	10 000
utilization category	A
performance class for circuit breaker	N
reference code / acc. to DIN 40719 extended according to IEC 204-2 / acc. to IEC 750	Q
operating frequency / maximum	120 1/s
Voltage	
Rated operational voltage U <sub>e</sub> / max.	690 V
<ul style="list-style-type: none"> <li>insulation voltage / rated value</li> <li>insulation voltage (U<sub>i</sub>) / at AC / rated value</li> </ul>	800 V
surge voltage resistance / rated value	8 kV
operating voltage	
<ul style="list-style-type: none"> <li>rated value / maximum</li> <li>for main current circuit / at AC / at 50 Hz / maximum</li> <li>for main current circuit / at AC / at 60 Hz / maximum</li> <li>for main current circuit / at DC / maximum</li> </ul>	690 V 690 V 690 V 500 V
Protection class	
protection class IP	IP20
protection function of the overcurrent release	LI
Current	
operational current	
<ul style="list-style-type: none"> <li>at 40 °C / rated value</li> <li>at 45 °C / rated value</li> <li>at 50 °C / rated value</li> <li>at 55 °C / rated value</li> <li>at 60 °C / rated value</li> <li>at 65 °C / rated value</li> <li>at 70 °C / rated value</li> </ul>	160 A 160 A 160 A 152 A 152 A 128 A 128 A
continuous current / rated value	160 A
derating temperature / for the rated value of the continuous current	50 °C
adjustable current response value current	
<ul style="list-style-type: none"> <li>of the current-dependent overload release / full-scale value</li> <li>of instantaneous short-circuit trip unit / minimum</li> <li>of instantaneous short-circuit trip unit / maximum</li> </ul>	160 A 200 A 1 760 A
Main circuit	
operating frequency	
<ul style="list-style-type: none"> <li>1 / rated value</li> <li>2 / rated value</li> </ul>	50 Hz 60 Hz

Auxiliary circuit	
number of CO contacts / for auxiliary contacts	0
number of NC contacts / for auxiliary contacts	1
number of NO contacts / for auxiliary contacts	2
Suitability	
suitability for use	system protection
Adjustable parameters	
adjustable current response value current / of the current-dependent overload release / initial value	64 A
Product details	
product component	
<ul style="list-style-type: none"> <li>• trip indicator</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• auxiliary switch</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• voltage trigger</li> </ul>	No
<ul style="list-style-type: none"> <li>• undervoltage release</li> </ul>	No
<ul style="list-style-type: none"> <li>• undervoltage release with leading contact</li> </ul>	No
product extension / optional / motor drive	Yes
Product function	
product function	
<ul style="list-style-type: none"> <li>• of thermal overload trip unit</li> </ul>	adjustable
<ul style="list-style-type: none"> <li>• grounding protection</li> </ul>	No
<ul style="list-style-type: none"> <li>• for neutral conductors / short-circuit and overload proof</li> </ul>	No
<ul style="list-style-type: none"> <li>• overload protection</li> </ul>	Yes
Short circuit	
breaking capacity operating short-circuit current (Ics)	
<ul style="list-style-type: none"> <li>• at 240 V / rated value</li> </ul>	150 kA
<ul style="list-style-type: none"> <li>• at 415 V / rated value</li> </ul>	75 kA
<ul style="list-style-type: none"> <li>• at 500 V / rated value</li> </ul>	38 kA
<ul style="list-style-type: none"> <li>• at 690 V / rated value</li> </ul>	6 kA
breaking capacity maximum short-circuit current (Icu)	
<ul style="list-style-type: none"> <li>• at 240 V / rated value</li> </ul>	200 kA
<ul style="list-style-type: none"> <li>• at 415 V / rated value</li> </ul>	100 kA
<ul style="list-style-type: none"> <li>• at 440 V / rated value</li> </ul>	75 kA
<ul style="list-style-type: none"> <li>• at 480 V / acc. to NEMA / rated value</li> </ul>	75 kA
<ul style="list-style-type: none"> <li>• at 500 V / rated value</li> </ul>	50 kA
<ul style="list-style-type: none"> <li>• at 600 V / acc. to NEMA / rated value</li> </ul>	12 kA
<ul style="list-style-type: none"> <li>• at 690 V / rated value</li> </ul>	12 kA
Connections	
arrangement of electrical connectors / for main current circuit	front side
type of connectable conductor cross-sections / for main contacts	
<ul style="list-style-type: none"> <li>• with flexible busbar</li> </ul>	12 x 10 mm
<ul style="list-style-type: none"> <li>• solid</li> </ul>	2.5 ... 95 mm <sup>2</sup>
<ul style="list-style-type: none"> <li>• finely stranded / with core end processing</li> </ul>	2.5 ... 50 mm <sup>2</sup>
<ul style="list-style-type: none"> <li>• stranded</li> </ul>	2.5 ... 95 mm <sup>2</sup>
type of connectable conductor cross-sections / for auxiliary contacts	
<ul style="list-style-type: none"> <li>• solid</li> </ul>	0.75 ... 1.5 mm <sup>2</sup>
<ul style="list-style-type: none"> <li>• finely stranded / with core end processing</li> </ul>	0,75 ... 1.0 mm <sup>2</sup>
type of electrical connection / for main current circuit	box terminal
Mechanical Design	
height	174.5 mm
width	104.5 mm
depth	106.5 mm
fastening method	fixed mounting
Environmental conditions	
ambient temperature / during operation	
<ul style="list-style-type: none"> <li>• minimum</li> </ul>	-25 °C

• maximum	70 °C
ambient temperature / during storage	
• minimum	-40 °C
• maximum	80 °C
<b>General Product Approval</b>	
<b>EMC</b>	



[Confirmation](#)

[Miscellaneous](#)

[TSE](#)



<b>Declaration of Conformity</b>	<b>Test Certificates</b>	<b>Marine / Shipping</b>			<b>other</b>
----------------------------------	--------------------------	--------------------------	--	--	--------------



[Special Test Certificate](#)



[Environmental Confirmations](#)

<b>other</b>
--------------

[Miscellaneous](#)

[Confirmation](#)

[Miscellaneous](#)

### Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VL2716-3SB33-0AD1>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/3VL2716-3SB33-0AD1>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3VL2716-3SB33-0AD1](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL2716-3SB33-0AD1)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

<http://www.siemens.com/specifications>



