

TRIP ALARM SWITCH CHANGEOVER CONTACTS  
TYPE HQ (7MM) ACCESSORY FOR 3VA1/2-  
BREAKER

Model		
product brandname		SENTRON
General technical data		
Thermal current	A	6
Overvoltage category		III
Voltage		
Insulation voltage / rated value	V	690
Surge voltage resistance / rated value	kV	4
<b>Operating voltage</b>		
• at AC / at 50 Hz / rated value / minimum	V	240
• at DC / rated value / minimum	V	250
<b>Wire stripping length</b>	mm	15
Connectable conductor cross-section / maximum	mm <sup>2</sup>	1.5
Tightening torque / with screw-type terminals / maximum	N·m	0.5
<b>Height</b>	mm	56
<b>Width</b>		
• Note		1 slot (7 mm)
<b>Depth</b>	mm	30
<b>Net weight</b>	g	30
<b>Degree of pollution</b>		3

General Product Approval	Declaration of Conformity	Test Certificates	other
--------------------------	---------------------------	-------------------	-------



[Typprüfbescheinigung/Werkszeugnis](#)

[sonstig](#)

## Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/3VA9988-0AB12>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<http://support.automation.siemens.com/WW/view/en/3VA9988-0AB12/all>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3VA9988-0AB12](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA9988-0AB12)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

<http://ausschreibungstexte.siemens.com/tiplv>

**last modified:**

10/14/2016