



CIRCUIT BREAKER 3VT2 HIGH BREAKING CAPACITY ICU=36KA, 415V AC 3-POLE; CIRCUIT BREAKER W/OVERCURRENT RELEASE SYSTEM PROTECTION ETU DP, LI IR= 40...100A, OVERLOAD PROTECTION IRM= 4... 8KA SHORT-CIRCUIT PROTECTION, WITHOUT AUXILIARY RELEASE WITHOUT AUXILIARY/ALARM SWITCH



Model		
product brandname		SENTRON
Product designation		3VT1_5 molded case circuit breakers
Design of the operating mechanism		toggle handle
Type of the driving mechanism / motor drive		No
Design of the overcurrent release		ETU DP

General technical data		
Number of poles		3
Size of the circuit-breaker		3VT2
Electrical endurance (switching cycles) / typical		3 000
Usage category		A
Performance class for circuit breaker		H
Mechanical service life (switching cycles) / typical		30 000
Operating frequency / maximum	1/h	120

Voltage		
Insulation voltage / rated value	V	690
Surge voltage resistance / rated value	kV	8

Protection class		
<b>Protection class IP</b>		IP40
<b>Protective function of the overcurrent release</b>		LI
Dissipation		
<b>Power loss [W]</b>		
<ul style="list-style-type: none"> <li>for rated value of the current / at AC / in hot operating state / per pole</li> </ul>	W	6
<ul style="list-style-type: none"> <li>maximum</li> </ul>	W	18
Electricity		
Continuous current / rated value	A	100
Derating temperature / for the rated value of the continuous current	°C	70
<b>Adjustable pick-up value current</b>		
<ul style="list-style-type: none"> <li>of the current-dependent overload release / Full-scale value</li> </ul>	A	100
<ul style="list-style-type: none"> <li>of instantaneous short-circuit trip unit / initial value</li> </ul>	A	400
<ul style="list-style-type: none"> <li>of instantaneous short-circuit trip unit / Full-scale value</li> </ul>	A	800
Main circuit		
<b>Operating frequency</b>		
<ul style="list-style-type: none"> <li>1 / rated value</li> </ul>	Hz	50
<ul style="list-style-type: none"> <li>2 / rated value</li> </ul>	Hz	60
<b>Operating voltage</b>		
<ul style="list-style-type: none"> <li>rated value / maximum</li> </ul>	V	690
<ul style="list-style-type: none"> <li>for main current circuit / at AC / at 50 Hz / maximum</li> </ul>	V	690
<ul style="list-style-type: none"> <li>for main current circuit / at AC / at 60 Hz / maximum</li> </ul>	V	690
<b>Operating current</b>		
<ul style="list-style-type: none"> <li>at 40 °C / rated value</li> </ul>	A	100
<ul style="list-style-type: none"> <li>at 50 °C / rated value</li> </ul>	A	100
<ul style="list-style-type: none"> <li>at 55 °C / rated value</li> </ul>	A	100
<ul style="list-style-type: none"> <li>at 60 °C / rated value</li> </ul>	A	100
<ul style="list-style-type: none"> <li>at 65 °C / rated value</li> </ul>	A	100
<ul style="list-style-type: none"> <li>at 70 °C / rated value</li> </ul>	A	100
Auxiliary circuit		
Number of CO contacts / for auxiliary contacts		0
<b>Number of NC contacts / for auxiliary contacts</b>		0
<b>Number of NO contacts / for auxiliary contacts</b>		0
Suitability		

<b>Suitability for use</b>		system protection
<ul style="list-style-type: none"> <li>• Disconnecting means</li> </ul>		Yes

### Adjustable parameters

<b>Adjustable pick-up value current / of the current-dependent overload release / initial value</b>	A	40
---	---	----

### Product details

<b>Product component</b>		
<ul style="list-style-type: none"> <li>• Trip indicator</li> <li>• Auxiliary switch</li> <li>• Voltage trigger</li> <li>• undervoltage release</li> <li>• undervoltage release with leading contact</li> </ul>		No No No No No
Product extension / optional / motor drive		Yes

### Product function

<b>Product function</b>		
<ul style="list-style-type: none"> <li>• of thermal overload trip unit</li> <li>• Ground fault protection</li> <li>• for neutral conductors / Short-circuit and overload proof</li> <li>• Phase failure detection</li> <li>• Overload protection</li> </ul>		adjustable No No No Yes

### Short circuit

<b>Operational short-circuit current breaking capacity (Ics)</b>		
<ul style="list-style-type: none"> <li>• at 240 V / rated value</li> <li>• at 415 V / rated value</li> <li>• at 500 V / rated value</li> <li>• at 690 V / rated value</li> </ul>	kA	50 36 13 8
<b>Maximum short-circuit current breaking capacity (Icu)</b>		
<ul style="list-style-type: none"> <li>• at 240 V / rated value</li> <li>• at 415 V / rated value</li> <li>• at 500 V / rated value</li> <li>• at 690 V / rated value</li> </ul>	kA	100 65 25 13

### Connections

Arrangement of electrical connectors / for main current circuit		front side
Type of electrical connection / for main current circuit		screw-type terminals

### Mechanical Design

<b>Height</b>	mm	225
<b>Width</b>	mm	105

Depth	mm	117
Mounting position		with vertical mounting surface +/-180° rotatable, with vertical mounting surface +/- 30° tiltable to the front and back
Mounting type		fixed mounting
Net weight	kg	0.317

#### Environmental conditions

<b>Ambient temperature</b>		
• during operation / minimum	°C	-40
• during operation / maximum	°C	70
• during storage / minimum	°C	-40
• during storage / maximum	°C	70

#### Certificates

<b>Equipment marking</b>		
• acc. to DIN EN 61346-2		Q
• acc. to DIN EN 81346-2		Q

<b>General Product Approval</b>	<b>Declaration of Conformity</b>	<b>Test Certificates</b>	<b>other</b>
---------------------------------	----------------------------------	--------------------------	--------------



[Typprüfbescheinigung/Werkszeugnis](#)

[Umweltbestätigung](#)

[sonstig](#)

#### Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/3VT2710-3AC36-0AA0>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<http://support.automation.siemens.com/WW/view/en/3VT2710-3AC36-0AA0/all>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3VT2710-3AC36-0AA0](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VT2710-3AC36-0AA0)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

<http://ausschreibungstexte.siemens.com/tiplv>

**last modified:**

10/14/2016