

SINAMICS BRAKING RESISTOR R=140Ohm P<sub>rated</sub>=200W  
P<sub>max</sub>=4000W/12s/5% duty STANDALONE



Order number	
Phase number / of the input voltage	Wert fehlt!
Type of voltage / of the input voltage	Wert fehlt!
Input voltage	Wert fehlt! ... Wert fehlt!
Consumed active power / rated value	0.2 kW
• maximum	4 kW
Type of electrical connection / for power cable	Terminal block
Connectable conductor cross-section / for power cable	2.5 mm <sup>2</sup>
Design of the temperature switch	Normally closed contact
Input voltage / of the temperature switch / at AC / maximum	Wert fehlt!
Input current / of the temperature switch / at AC / maximum	2.5 A
Connectable conductor cross-section / on the temperature switch / maximum	2.5 mm <sup>2</sup>
Type of electrical connection / of the protective conductor connection	Yes
Design of the protective conductor connection / on enclosure	M4 screw
Protection class IP	IP20

Electrical resistance / of the braking resistor	140 Ω
Width	105 mm
Height	345 mm
Depth	100 mm
Net weight	1.8 kg

#### Further information

**Information und Download Center**

[https://www.automation.siemens.com/mcms/infocenter/content/en/Pages/order\\_form.aspx](https://www.automation.siemens.com/mcms/infocenter/content/en/Pages/order_form.aspx)

**Technical documentation**

<http://w3.siemens.com/mcms/mc-solutions/en/motion-control/support/technical-documentation/Pages/technical-documentation.aspx>

**Industry Mall**

<https://eb.automation.siemens.com/mall/en/WW/Catagog/Product/6SL3201-0BE21-0AA0/all>

**Industry Online Support**

<http://support.automation.siemens.com/WW/view/en/6SL3201-0BE21-0AA0/all>