



SIRIUS ACT with PROFINET: standard interface module 24 V DC, spring-loaded terminal, front plate mounting 1 to 20 terminal modules connectable

product brand name	SIRIUS ACT
product designation	Interface module for PROFINET
product type designation	3SU1
Display	
display version	
<ul style="list-style-type: none"> for diagnostic function: Supply voltage monitoring power LED 	Yes
<ul style="list-style-type: none"> status Tx/Rx link 	Yes
General technical data	
product function	
<ul style="list-style-type: none"> reverse polarity protection 	Yes
<ul style="list-style-type: none"> diagnostics function 	Yes
<ul style="list-style-type: none"> alarms 	Yes
<ul style="list-style-type: none"> I&M data 	Yes; I&M0 ... I&M3
firmware version	2.1.1
hardware version	1
configuration function with dataset	Yes
software version with STEP 7 in the TIA Portal required	Integrated in TIA Portal Version 14 SP1 or higher (HSP for V13 and V14)
number of units per rack maximum	20
number of submodules per station maximum	24
power loss [W] typical	0.67 W
insulation voltage rated value	30 V
degree of pollution	3
type of voltage	
<ul style="list-style-type: none"> of the operating voltage 	DC
<ul style="list-style-type: none"> of the input voltage 	DC
surge voltage resistance rated value	0.8 kV
consumed current	
<ul style="list-style-type: none"> maximum 	100 mA
<ul style="list-style-type: none"> rated value 	28 mA
protection class IP	IP20
reference code according to IEC 81346-2	K
Substance Prohibitance (Date)	12/19/2016
operating voltage rated value	20.4 V
I²t value	0.008 A ² ·s
Supply voltage	
supply voltage at DC rated value	24 V
Communication/ Protocol	
protocol is supported	

<ul style="list-style-type: none"> • PROFINET IO protocol 	Yes
<ul style="list-style-type: none"> • PROFI-safe protocol 	No
product function at the Ethernet interface	
<ul style="list-style-type: none"> • Autocrossover 	Yes
<ul style="list-style-type: none"> • Autonegotiation 	Yes
protocol at the 1st interface media redundancy protocol	No
product function at the 1st interface PROFINET IO device	Yes
product function of the PROFINET IO device is supported PROFINET system redundancy	No
service as PROFINET IO device	
<ul style="list-style-type: none"> • prioritized startup 	No
<ul style="list-style-type: none"> • isochronous mode 	No
<ul style="list-style-type: none"> • supports Shared Device 	No
<ul style="list-style-type: none"> • supports PROFIenergy 	No
<ul style="list-style-type: none"> • IRT 	No
<ul style="list-style-type: none"> • MRP 	No
<ul style="list-style-type: none"> • MRPD 	No
service for open IE communication	
<ul style="list-style-type: none"> • LLDP 	Yes
<ul style="list-style-type: none"> • SNMP 	Yes
<ul style="list-style-type: none"> • TCP/IP 	Yes
GSD version/revision with PROFINET required	V2.3
transmission mode for Industrial Ethernet	PROFINET with 100 Mbps full duplex (100BASE-TX)
network load class according to PROFINET	1
specification for Security Level 1 test according to PROFINET	Resilient to network loading
Control circuit/ Control	
inrush current maximum	16 A
Galvanic isolation	
galvanic isolation between PROFINET and all other circuits	Yes
Inputs/ Outputs	
number of digital inputs	0
<ul style="list-style-type: none"> • safety-related 	0
number of digital outputs	0
Connections/ Terminals	
type of electrical connection	spring-loaded terminals
connectable conductor cross-section for auxiliary contacts	
<ul style="list-style-type: none"> • solid or stranded 	0.2 ... 2.5 mm ²
<ul style="list-style-type: none"> • finely stranded with core end processing 	2.5 mm ²
connectable conductor cross-section	
<ul style="list-style-type: none"> • solid 	0.2 ... 2.5 mm ²
<ul style="list-style-type: none"> • solid with core end processing 	0.2 ... 2.5 mm ²
<ul style="list-style-type: none"> • finely stranded with core end processing 	0.25 ... 2.5 mm ²
<ul style="list-style-type: none"> • finely stranded without core end processing 	0.2 ... 2.5 mm ²
AWG number as coded connectable conductor cross section	30 ... 12
tightening torque with screw-type terminals	0.5 ... 0.6 N·m
Safety related data	
service life maximum	20 y
design of the interface	
<ul style="list-style-type: none"> • Ethernet interface 	Yes; for Ethernet services
<ul style="list-style-type: none"> • Fast Ethernet interface 	Yes; PROFINET with 100 Mbps
interface design 1	
<ul style="list-style-type: none"> • integrated switch 	No
<ul style="list-style-type: none"> • RJ45 (Ethernet) 	Yes
number of ports at the 1st interface	1
number of interfaces according to PROFINET	1
Ambient conditions	

ambient temperature	
<ul style="list-style-type: none"> during operation during storage 	-25 ... +60 °C -40 ... +80 °C
environmental category during operation according to IEC 60721	3M6, 3S2, 3B2, 3K6 (with relative air humidity of 10 ... 95%, no condensation in operation permitted)
explosion protection marking for intrinsic safety of related equipment EEx ia	No
explosion protection marking for intrinsic safety of related equipment EEx ib	No

Installation/ mounting/ dimensions

fastening method of modules and accessories	Front plate mounting
height	80.1 mm
width	40 mm
depth	72.1 mm

Certificates/ approvals

General Product Approval	Declaration of Conformity	Test Certificates
--------------------------	---------------------------	-------------------

[Confirmation](#)



[UK Declaration of Conformity](#)

[Special Test Certificate](#)

Test Certificates	other
-------------------	-------

[Type Test Certificates/Test Report](#)

[Confirmation](#)



[PROFINET-Certification](#)

[PROIsafe-Certification](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1400-1LK10-3AA1>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1400-1LK10-3AA1>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SU1400-1LK10-3AA1>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1400-1LK10-3AA1&lang=en



