

circuit breaker VL630N standard breaking capacity I_{cu}=55kA, 415V AC 3-pole, line protection trip unit TM, LI I_n=630A, rated current I_R=500...630A, overload protection, I_I=3250...6500A, short-circuit protection Shunt release 110...127 V DC Auxiliary/alarm switch mounting kit 2 AUX (1 NO+1 NC)+1 AS (1 NO)

Model	
type of the driving mechanism / motor drive	No
design of the overcurrent release	TM
General technical data	
number of poles	3
size of the circuit-breaker	3VL5
mechanical service life (switching cycles) / typical	10 000
electrical endurance (switching cycles) / typical	5 000
utilization category	A
performance class for circuit breaker	N
reference code / according to DIN 40719 extended according to IEC 204-2 / according to IEC 750	Q
operating frequency / maximum	60 1/s
Voltage	
Rated operational voltage U _e / max.	690 V
<ul style="list-style-type: none"> insulation voltage / rated value insulation voltage (U_i) / at AC / rated value 	800 V
surge voltage resistance / rated value	8 kV
operating voltage	
<ul style="list-style-type: none"> rated value / maximum for main current circuit / at AC / at 50 Hz / maximum for main current circuit / at AC / at 60 Hz / maximum 	690 V
Protection class	
protection class IP	IP20
protection function of the overcurrent release	LI
Current	
operational current	
<ul style="list-style-type: none"> at 40 °C / rated value at 45 °C / rated value at 50 °C / rated value at 55 °C / rated value at 60 °C / rated value at 65 °C / rated value at 70 °C / rated value 	630 A
continuous current / rated value	630 A
derating temperature / for the rated value of the continuous current	50 °C
adjustable current response value current	
<ul style="list-style-type: none"> of the current-dependent overload release / full-scale value of instantaneous short-circuit trip unit / minimum of instantaneous short-circuit trip unit / maximum 	630 A
	3 150 A
	6 300 A
Main circuit	
operating frequency	
<ul style="list-style-type: none"> 1 / rated value 2 / rated value 	50 Hz
	60 Hz
Auxiliary circuit	
number of CO contacts / for auxiliary contacts	0

number of NC contacts / for auxiliary contacts	1
number of NO contacts / for auxiliary contacts	2
Suitability	
suitability for use	system protection
Adjustable parameters	
adjustable current response value current / of the current-dependent overload release / initial value	504 A
Product details	
product component	
• trip indicator	Yes
• auxiliary switch	Yes
• voltage trigger	Yes
• undervoltage release	No
• undervoltage release with leading contact	No
product extension / optional / motor drive	Yes
Product function	
product function	
• of thermal overload trip unit	adjustable
• grounding protection	No
• for neutral conductors / short-circuit and overload proof	No
• overload protection	Yes
Short circuit	
breaking capacity operating short-circuit current (Ics)	
• at 240 V / rated value	65 kA
• at 415 V / rated value	55 kA
• at 500 V / rated value	20 kA
• at 690 V / rated value	10 kA
breaking capacity maximum short-circuit current (Icu)	
• at 240 V / rated value	65 kA
• at 415 V / rated value	55 kA
• at 440 V / rated value	35 kA
• at 480 V / according to NEMA / rated value	25 kA
• at 500 V / rated value	25 kA
• at 600 V / according to NEMA / rated value	20 kA
• at 690 V / rated value	20 kA
Connections	
arrangement of electrical connectors / for main current circuit	front side
type of connectable conductor cross-sections / for auxiliary contacts	
• solid	0.75 ... 1.5 mm ²
• finely stranded / with core end processing	0,75 ... 1.0 mm ²
type of electrical connection / for main current circuit	screw-type terminals
Mechanical Design	
height	279.5 mm
width	190 mm
depth	138.5 mm
fastening method	fixed mounting
Environmental conditions	
ambient temperature / during operation	
• minimum	0 °C
• maximum	70 °C
ambient temperature / during storage	
• minimum	-40 °C
• maximum	80 °C
General Product Approval	EMC

[Miscellaneous](#)

[Confirmation](#)



[TSE](#)



Declaration of Conformity

Test Certificates

Marine / Shipping

[UK Declaration of Conformity](#)



EG-Konf.

[Special Test Certificate](#)



ABS



BUREAU VERITAS



LRS

Marine / Shipping

other



PRS



RINA



RMRS



DNV-GL

[Environmental Confirmations](#)

[Miscellaneous](#)

other

[Confirmation](#)

[Miscellaneous](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VL5763-1DC36-8KE1>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3VL5763-1DC36-8KE1>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL5763-1DC36-8KE1

CAx-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



