

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV3090A

SIMOTICS GP - 90 S - IM B5 - 2p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	η ³⁾			$\cos\phi$ ³⁾			I_A/I_N I_I/I_N	M_A/M_N T_I/T_N	M_K/M_N T_B/T_N	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4				
DOL duty (S1) - 155(F) to 130(B)																	
220	Δ	60	1.50	-/-	5.50	3525	4.0	85.5	84.8	82.3	0.84	0.77	0.66	9.8	3.1	4.9	IE3
380	Y	60	1.50	-/-	3.15	3525	4.0	85.5	84.8	82.3	0.84	0.77	0.66	9.8	3.1	4.9	IE3
IM B5 / IM 3001		FS 90 S		IP55		IEC/EN 60034		IEC, DIN, ISO, VDE, EN			KS C IEC60034-2-1						
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 8 s 10.7 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	65 / 77 dB(A) ^{2) 3)}	69 / 81 dB(A) ^{2) 3)}	Vibration severity grade	A
Moment of inertia	0.0021 kg m ²		Thermal class	F
Bearing DE NDE	6205 2Z C3	6004 2Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L_{10mh} , $F_{Rad min}$ 50 60Hz ¹⁾ for coupling operation	40000 h	32000 h	Frame material	aluminum
Lubricants	Unirex N3		Net weight of the motor (IM B3)	15 kg
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Preloaded bearing DE		Motor protection	(A) without (Standard)
Condensate drainage holes	No		Method of cooling	IC411 - self ventilated, surface cooled
External earthing terminal	No			

Terminal box

Terminal box position	top	Max. cross-sectional area	1.5 mm ²
Material of terminal box	Aluminium	Cable diameter from ... to ...	9 mm - 17 mm
Type of terminal box	TB1 E00	Cable entry	1xM25x1,5
Contact screw thread	M4	Cable gland	1 plug

Notes:

I_A/I_N = locked rotor current / current nominal
 M_A/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque
 1) L10mh according to DIN ISO 281 10/2010
 2) at rated power / at full load
 3) Value is valid only for DOL operation with motor design IC411

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	<i>Technical data are subject to change! There may be discrepancies between calculated and rating plate values.</i>	Link documents
	document type datasheet	document status released			document number
	title 1LE1043-0EA09-0FA4-Z D33+M2A	rev. 01	creation date 2022-07-26		
© Siemens AG 2022					

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS




Motor type : 1AV3090A

SIMOTICS GP - 90 S - IM B5 - 2p

Special design

D33 For Korea, certified according to KS C IEC 60034-2-1 M2A 220 VDI/380 VY; 60Hz, 50-Hz power

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	<i>Technical data are subject to change! There may be discrepancies between calculated and rating plate values.</i>	Link documents
SIEMENS	document type datasheet	document status released			
	title 1LE1043-0EA09-0FA4-Z D33+M2A	document number			
© Siemens AG 2022	rev. 01	creation date 2022-07-26	language en	Page 2/2	