

# Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV3094B SIMOTICS GP - 90 L - IM B5 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project
Remarks		

## Electrical data

## Safe Area

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	η <sup>3)</sup>			cosφ <sup>3)</sup>			I <sub>A</sub> /I <sub>N</sub> I <sub>I</sub> /I <sub>N</sub>	M <sub>A</sub> /M <sub>N</sub> T <sub>I</sub> /T <sub>N</sub>	M <sub>K</sub> /M <sub>N</sub> T <sub>B</sub> /T <sub>N</sub>	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4				
<b>DOL duty (S1) - 155(F) to 130(B)</b>																	
230	Δ	50	1.50	-/-	5.50	1445	9.9	85.3	85.7	84.4	0.80	0.73	0.60	7.3	2.9	3.5	IE3
400	Y	50	1.50	-/-	3.15	1445	9.9	85.3	85.7	84.4	0.80	0.73	0.60	7.3	2.9	3.5	IE3
460	Y	60	1.75	-/-	3.15	1740	9.6	86.5	86.7	85.4	0.80	0.74	0.62	7.7	2.9	3.7	IE3
460	Y	60	1.50	-/-	2.85	1755	8.2	86.5	86.6	84.7	0.77	0.69	0.57	8.6	3.4	4.3	IE3
IM B5 / IM 3001		FS 90 L		IP55		IEC/EN 60034		IEC, DIN, ISO, VDE, EN						KS C IEC60034-2-1			
Environmental conditions : -20 °C - +40 °C / 1,000 m										Locked rotor time (hot / cold) : 17.3 s   21.5 s							

## Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	56 / 68 dB(A) <sup>2) 3)</sup>	58 / 70 dB(A) <sup>2) 3)</sup>	Vibration severity grade	A
Moment of inertia	0.0049 kg m <sup>2</sup>		Thermal class	F
Bearing DE   NDE	6205 2Z C3	6004 2Z C3	Duty type	S1
<b>bearing lifetime</b>			Direction of rotation	bidirectional
L <sub>10mh</sub> , F <sub>Rad min</sub> 50 60Hz <sup>1)</sup> for coupling operation	40000 h	32000 h	Frame material	aluminum
Lubricants	Unirex N3		Net weight of the motor (IM B3)	19 kg
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Preloaded bearing DE		Motor protection	(A) without (Standard)
Condensate drainage holes	No		Method of cooling	IC411 - self ventilated, surface cooled
External earthing terminal	No			

## Terminal box

Terminal box position	top	Max. cross-sectional area	1.5 mm <sup>2</sup>
Material of terminal box	Aluminium	Cable diameter from ... to ...	9 mm - 17 mm
Type of terminal box	TB1 E00	Cable entry	1xM25x1,5
Contact screw thread	M4	Cable gland	1 plug

## Notes:

I<sub>A</sub>/I<sub>N</sub> = locked rotor current / current nominal  
 M<sub>A</sub>/M<sub>N</sub> = locked rotor torque / torque nominal  
 M<sub>K</sub>/M<sub>N</sub> = break down torque / nominal torque  
 1) L10mh according to DIN ISO 281 10/2010  
 2) at rated power / at full load  
 3) Value is valid only for DOL operation with motor design IC411

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	<a href="#">Link documents</a>
	document type datasheet	document status released			
	title 1LE1043-0EB42-2FA4-Z	document number			
© Siemens AG 2022	rev. D33	creation date 2022-08-22	language en		

**Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS**




Motor type : 1AV3094B

SIMOTICS GP - 90 L - IM B5 - 4p

**Special design**

D33 For Korea, certified according to KS C IEC 60034-2-1

**Notes:**

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	<i>Technical data are subject to change! There may be discrepancies between calculated and rating plate values.</i>	<a href="#">Link documents</a>
<b>SIEMENS</b>	document type datasheet	document status released			
	title 1LE1043-0EB42-2FA4-Z D33	document number			
© Siemens AG 2022	rev. 01	creation date 2022-08-22	language en	Page 2/2	