

Data sheet for SIMOTICS S-1FK7



Figure similar

MLFB-Ordering data

1FK7060-2AC71-1QB0

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Engineering data

Rated speed (100 K) 2000 rpm

Number of poles 8

Rated torque (100 K) 5.3 Nm

Rated current 3.0 A

Static torque (60 K) 5.00 Nm

Static torque (100 K) 6.00 Nm

Stall current (60 K) 2.55 A

Stall current (100 K) 3.15 A

Moment of inertia 8.700 kgcm²

Efficiency 90.0 %

Physical constants

Torque constant 1.91 Nm/A

Voltage constant at 20° C 121.0 V/1000*min⁻¹

Winding resistance at 20° C 2.75 Ω

Rotating field inductance 30.5 mH

Electrical time constant 11.10 ms

Mechanical time constant 1.75 ms

Thermal time constant 30 min

Shaft torsional stiffness 28500 Nm/rad

Net weight of the motor 8.5 kg

Mechanical data

Motor type Permanent-magnet synchronous motor

Motor type Compact

Shaft height 63

Cooling Natural cooling

Radial runout tolerance 0.040 mm

Concentricity tolerance 0.10 mm

Axial runout tolerance 0.10 mm

Vibration severity grade Grade A

Connector size 1

Degree of protection IP64

Design acc. to Code I IM B5 (IM V1, IM V3)

Temperature monitoring Pt1000 temperature sensor

Electrical connectors Connectors for signals and power rotatable

Color of the housing Standard (Anthracite RAL 7016)

Holding brake with holding brake

Shaft end Feather key

Encoder system Encoder AS20DQI: absolute encoder single-turn 20 bits



Figure similar

MLFB-Ordering data

1FK7060-2AC71-1QB0

Optimum operating point

Optimum speed	2000 rpm
Optimum power	1.1 kW

Limiting data

Max. permissible speed (mech.)	7200 rpm
Max. permissible speed (inverter)	4750 rpm
Maximum torque	18.0 Nm
Maximum current	10.7 A

Holding brake

Holding brake version	Permanent-magnet brake
Holding torque	13.0 Nm
Power supply voltage	DC 24 V \pm 10 %
Coil current	0.8 A
Opening time	100 ms
Closing time	50 ms
Highest braking work	380 J

Recommended Motor Module

Rated inverter current	3 A
Maximum inverter current	9 A
Maximum torque	15.90 Nm