

# Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV3073A

SIMOTICS GP - 71 M - IM B14 - 2p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project
Remarks		

## Electrical data

## Safe Area

U [V]	$\Delta / Y$	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	$\eta^{3)}$			$\cos\phi^{3)}$			$I_A/I_N$ $I_f/I_N$	$M_A/M_N$ $T_f/T_N$	$M_K/M_N$ $T_B/T_N$	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4				
<b>DOL duty (S1) - 155(F) to 155(F)</b>																	
230	$\Delta$	50	0.55	-/-	2.35	2850	1.8	77.8	77.5	74.5	0.76	0.67	0.54	6.1	3.7	3.7	IE3
400	Y	50	0.55	-/-	1.34	2850	1.8	77.8	77.5	74.5	0.76	0.67	0.54	6.1	3.7	3.7	IE3
460	Y	60	0.63	-/-	1.35	3450	1.7	76.8	76.1	72.9	0.76	0.68	0.55	6.6	3.9	3.9	IE3
460	Y	60	0.55	0.75	1.25	3470	1.5	76.8	75.3	71.0	0.73	0.64	0.51	7.2	4.5	4.5	MG1
IM B14 / IM 3601		FS 71 M		IP55		UKCA		IEC/EN 60034		IEC, EN, UL, CSA, NEMA MG1-12			kVA Code: M				
Environmental conditions : -20 °C - + °C / 1,000 m										Locked rotor time (hot / cold) : 22.9 s   28.9 s							

## Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	57 / 68 dB(A) <sup>2) 3)</sup>	62 / 73 dB(A) <sup>2) 3)</sup>	Vibration severity grade	A
Moment of inertia	0.0006 kg m <sup>2</sup>		Thermal class	F
Bearing DE   NDE	6202 2Z C3	6202 2Z C3	Duty type	S1
<b>bearing lifetime</b>			Direction of rotation	bidirectional
$L_{10mh}$ , $F_{Rad}$ min 50 60Hz <sup>1)</sup> for coupling operation	40000 h	32000 h	Frame material	aluminum
Regreasing device	Without		Net weight of the motor (IM B3)	8 kg
Grease nipple	-/-		Coating (paint finish)	Standard paint finish C2
Type of bearing	Preloaded bearing DE		Color, paint shade	RAL7030
Condensate drainage holes	Without		Motor protection	(A) without (Standard)
External earthing terminal	Without		Method of cooling	IC411 - self ventilated, surface cooled

## Terminal box

Terminal box position	top	Max. cross-sectional area	1.5 mm <sup>2</sup>
Material of terminal box	Aluminium	Cable diameter from ... to ...	9 mm - 17 mm
Type of terminal box	TB1 B10	Cable entry	1xM25x1,5
Contact screw thread	M4	Cable gland	1 plug

## Notes:

$I_A/I_N$  = locked rotor current / current nominal      1) L10mh according to DIN ISO 281 10/2010      3) Value is valid only for DOL operation with motor design IC411  
 $M_A/M_N$  = locked rotor torque / torque nominal      2) at rated power / at full load

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	<i>Technical data are subject to change! There may be discrepancies between calculated and rating plate values.</i>	<a href="#">Link documents</a>	
	document type datasheet	document status released				
	title 1LE1023-OCA32-2KA4-Z N03	document number				
© Siemens AG 2023	rev. 943	creation date 2023-05-25	language en			Page 1/2

# Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS




Motor type : 1AV3073A

SIMOTICS GP - 71 M - IM B14 - 2p

## Special design

N03 Temperature class 155 (F), utilised to 155 (F), with increased cooling medium temperature

## Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	<i>Technical data are subject to change! There may be discrepancies between calculated and rating plate values.</i>	<a href="#">Link documents</a>
<b>SIEMENS</b>	document type datasheet	document status released			
	title 1LE1023-0CA32-2KA4-Z N03	document number			
© Siemens AG 2023	rev. 943	creation date 2023-05-25	language en	Page 2/2	