

## Data sheet for braking resistor

Article No.: JJY:023423320001

Client order no. : Order no. : Offer no. : Remarks :

| Rated data                       |                   |  |
|----------------------------------|-------------------|--|
| Rated power P <sub>DB</sub>      | 1.5 kW            |  |
| Rated power, max. 1)             | 30 kW             |  |
|                                  |                   |  |
| General technical specifications |                   |  |
| Resistance                       | 4.5 Ω             |  |
| DC-link voltage, max.            | 420 V             |  |
|                                  |                   |  |
| Mechanical data                  |                   |  |
| Degree of protection             | IP21              |  |
| Net weight                       | 8.5 kg (18.74 lb) |  |
| Dimensions                       |                   |  |
| Width                            | 220 mm (8.66 in)  |  |
| Height                           | 180 mm (7.09 in)  |  |
| Denth                            | 560 mm (22 05 in) |  |

<sup>&</sup>lt;sup>1)</sup>Load duration for peak power 12 s, for a braking duty cycle period of 240 s.



Figure similar

Item no. : Consignment no. : Project :

| Standards                        |                        |  |
|----------------------------------|------------------------|--|
| Compliance with standards        | CE / UL / CSA          |  |
| Connections                      |                        |  |
| Power connection                 |                        |  |
| Version                          | Terminal block         |  |
| Conductor cross-section          | 16.0 mm² (AWG 6)       |  |
| Thermostatic switch              |                        |  |
| Version                          | integrated             |  |
| Conductor cross-section          | 1.5 mm² (AWG 16)       |  |
| Environmental conditions         |                        |  |
| Cooling method                   | natural convection     |  |
| Ambient temperature in operation | -25 40 °C (-13 104 °F) |  |