

MLFB-Ordering data

6FC5303-1AF10-0AA0



Figure similar

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Rated data

Input voltage DC 24 V

Power consumption, max. 25.0 W

Mechanical data

Net weight 3.000 kg (6.61 lb)

Width 483.0 mm (19.02 in)

Height 155.0 mm (6.10 in)

Depth 165.0 mm (6.50 in)

Installation depth 105.0 mm (4.13 in)

Mounting surface

Cutout width 451.0 mm (17.76 in)

Cutout height 137.6 mm (5.42 in)

Degree of protection

Rear side IP10A

Front side IP54

Ambient conditions

Climate class according to EN60721-3-3 Condensation and icing excluded. Low air temperature 0 °C (32 °F).

Ambient temperature

Operation on the front 0 ... 45 °C (32 ... 113 °F)

Operation at the rear 0 ... 55 °C (32 ... 131 °F)

Transport -40 ... 70 °C (-40 ... 158 °F)

Storage -25 ... 55 °C (-13 ... 131 °F)

Relative humidity

Operation 5 ... 95 %

Storage 5 ... 95 %

Transport 5 ... 95 %

Approvals

Certificate of suitability CE, UL