

# Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV2063B

SIMOTICS GP - 63 M - IM B5 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

## Safe Area

-/-

## Electrical data

U	$\Delta / Y$	f	P	P	I	n	M	$\eta^{3)}$			$\cos\phi^{3)}$			$I_A/I_N$	$M_A/M_N$	$M_K/M_N$	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	$I_i/I_N$	$T_i/T_N$	$T_B/T_N$	

DOL duty (S1) - 155(F) to 130(B)

IM B5 / IM 3001	FS 63 M	IP55	UKCA	IEC/EN 60034	IEC, DIN, ISO, VDE, EN
-----------------	---------	------	------	--------------	------------------------

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 36.3 s | 47.7 s

## Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	/ dB(A) <sup>2) 3)</sup>	/ dB(A) <sup>2) 3)</sup>	Vibration severity grade	A
Moment of inertia	0.0004 kg m <sup>2</sup>		Thermal class	F
Bearing DE   NDE	6201 2Z C3	6201 2Z C3	Duty type	S1
<b>bearing lifetime</b>			Direction of rotation	bidirectional
$L_{10mh} F_{Rad, min}$ for coupling operation 50 60Hz <sup>1)</sup>	40000 h	32000 h	Frame material	aluminum
Regreasing device	Without		Net weight of the motor (IM B3)	kg
Grease nipple	-/-		Coating (paint finish)	Standard paint finish C2
Type of bearing	Preloaded bearing DE		Color, paint shade	RAL7030
Condensate drainage holes	Without		Motor protection	(A) without (Standard)
External earthing terminal	Without		Method of cooling	IC411 - self ventilated, surface cooled

## Terminal box

Terminal box position	top	Max. cross-sectional area	1.5 mm <sup>2</sup>
Material of terminal box	Aluminium	Cable diameter from ... to ...	9 mm - 17 mm
Type of terminal box	TB1 B00	Cable entry	1xM25x1,5
Contact screw thread	M4	Cable gland	1 plug

## Notes:

$I_A/I_N$  = locked rotor current / current nominal  
 $M_A/M_N$  = locked rotor torque / torque nominal  
 $M_K/M_N$  = break down torque / nominal torque  
 1) L10mh according to DIN ISO 281 10/2010  
 2) at rated power / at full load  
 3) Value is valid only for DOL operation with motor design IC411

responsible dep. IN LVM	technical reference	created by SPC	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	<a href="#">Link documents</a>
	document type datasheet	document status released			document number
	title 1LE1001-0BB39-0FA4 M1Y	rev. 950	creation date 2023-10-24		
© INNOMOTICS 2023					

**Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS**




Motor type : 1AV2063B

SIMOTICS GP - 63 M - IM B5 - 4p

**Special design**

M1Y Non-standard winding:

**Notes:**

responsible dep. IN LVM	technical reference	created by SPC	approved by	<i>Technical data are subject to change! There may be discrepancies between calculated and rating plate values.</i>	<a href="#">Link documents</a>
<b>SIEMENS</b>	document type datasheet	document status released			
	title 1LE1001-0BB39-0FA4 M1Y	document number			
© INNOMOTICS 2023	rev. 950	creation date 2023-10-24	language en	Page 2/2	