

product description

Flexible bus cable (4-core), preferred length, unassembled

Industrial Ethernet FC TP flexible cable GP 2x2; (PROFINET type B); TP installation cable with flexible cores; 4-core; shielded; Cat5e for connection to IE FC RJ45 Plug 2x 2, AWG22; 1000 m.



suitability for use	For occasionally moved machine parts
cable designation	2YY (ST) CY 2x2x0,75/1,5-100 LI GN SF/UTP
wire length	1000 m
<b>electrical data</b>	
attenuation factor per length	
• at 10 MHz / maximum	0.06 dB/m
• at 100 MHz / maximum	0.21 dB/m
impedance	
• at 1 MHz ... 100 MHz	100 Ω
relative symmetrical tolerance	
• of the characteristic impedance at 1 MHz ... 100 MHz	15 %
near-end crosstalk per length	
• at 1 MHz ... 100 MHz	0.5 dB/m
transfer impedance per length / at 10 MHz	20 mΩ/m
loop resistance per length / maximum	120 mΩ/m
operating voltage	
• RMS value	80 V
NVP value in percent	66 %
<b>mechanical data</b>	
number of electrical cores	4
design of the shield	Overlapped aluminum-clad foil, sheathed in a braided screen of tin-plated copper wires
type of electrical connection / FastConnect	Yes
core diameter	
• of AWG22 insulated conductor	0.75 mm
outer diameter	
• of inner conductor	0.75 mm
• of the wire insulation	1.5 mm
• of the inner sheath of the cable	3.9 mm
• of cable sheath	6.5 mm
symmetrical tolerance of the outer diameter / of cable sheath	0.2 mm
material	
• of the wire insulation	polyethylene (PE)
• of the inner sheath of the cable	PVC
• of cable sheath	PVC
color	
• of the insulation of data wires	white/yellow/blue/orange
• of cable sheath	green
bending radius	

<ul style="list-style-type: none"> <li>• with single bend / minimum permissible</li> </ul>	32.5 mm
<ul style="list-style-type: none"> <li>• with multiple bends / minimum permissible</li> </ul>	52 mm
tensile load / maximum	150 N
weight per length	68 kg/km
<b>ambient conditions</b>	
ambient temperature	
<ul style="list-style-type: none"> <li>• during operation</li> </ul>	-25 ... +75 °C
<ul style="list-style-type: none"> <li>• during storage</li> </ul>	-25 ... +75 °C
<ul style="list-style-type: none"> <li>• during transport</li> </ul>	-25 ... +75 °C
<ul style="list-style-type: none"> <li>• during installation</li> </ul>	-10 ... +60 °C
<ul style="list-style-type: none"> <li>• note</li> </ul>	Electrical properties measured at 20 °C, tests according to DIN VDE 0472
fire behavior	flame resistant according to UL 1685 (CSA FT 4)
class of burning behaviour / according to EN 13501-6	Eca
chemical resistance	
<ul style="list-style-type: none"> <li>• to mineral oil</li> </ul>	oil resistant according to IEC 60811-404 (7x24h/90°C)
<ul style="list-style-type: none"> <li>• to grease</li> </ul>	Conditional resistance
<ul style="list-style-type: none"> <li>• to water</li> </ul>	conditional resistance
radiological resistance / to UV radiation	resistant
<b>product features, product functions, product components / general</b>	
product feature	
<ul style="list-style-type: none"> <li>• halogen-free</li> </ul>	No
<ul style="list-style-type: none"> <li>• silicon-free</li> </ul>	Yes
wire length / for Industrial Ethernet	
<ul style="list-style-type: none"> <li>• with 100BaseTX</li> </ul>	85 m
<b>standards, specifications, approvals</b>	
UL/ETL listing / 300 V Rating	Yes; c(ETL)us, CMG / (ETL)us PLTC / Sun Res / OIL RES
UL/ETL style / 600 V Rating	Yes; cRUus AWM 21694 AWM I A/B 60°C 600V FT2
certificate of suitability	
<ul style="list-style-type: none"> <li>• EAC approval</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• CE marking</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• RoHS conformity</li> </ul>	Yes
standard for structured cabling	Cat5e
Marine classification association	
<ul style="list-style-type: none"> <li>• American Bureau of Shipping Europe Ltd. (ABS)</li> </ul>	No
<ul style="list-style-type: none"> <li>• French marine classification society (BV)</li> </ul>	No
<ul style="list-style-type: none"> <li>• Det Norske Veritas (DNV)</li> </ul>	No
<ul style="list-style-type: none"> <li>• Germanische Lloyd (GL)</li> </ul>	No
<ul style="list-style-type: none"> <li>• Lloyds Register of Shipping (LRS)</li> </ul>	No
<ul style="list-style-type: none"> <li>• Nippon Kaiji Kyokai (NK)</li> </ul>	No
<ul style="list-style-type: none"> <li>• Polski Rejestr Statkow (PRS)</li> </ul>	No
reference code	
<ul style="list-style-type: none"> <li>• according to IEC 81346-2</li> </ul>	WG
<ul style="list-style-type: none"> <li>• according to IEC 81346-2:2019</li> </ul>	WGB
<b>further information / internet links</b>	
internet link	
<ul style="list-style-type: none"> <li>• to web page: selection aid TIA Selection Tool</li> </ul>	<a href="http://www.siemens.com/tia-selection-tool">http://www.siemens.com/tia-selection-tool</a>
<ul style="list-style-type: none"> <li>• to website: Industrial communication</li> </ul>	<a href="http://www.siemens.com/simatic-net">http://www.siemens.com/simatic-net</a>
<ul style="list-style-type: none"> <li>• to website: Industry Mall</li> </ul>	<a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a>
<ul style="list-style-type: none"> <li>• to website: Information and Download Center</li> </ul>	<a href="http://www.siemens.com/industry/infocenter">http://www.siemens.com/industry/infocenter</a>
<ul style="list-style-type: none"> <li>• to website: Selection guide for cables and connectors</li> </ul>	<a href="https://sie.ag/2QdlxcP">https://sie.ag/2QdlxcP</a>
<ul style="list-style-type: none"> <li>• to website: Image database</li> </ul>	<a href="http://automation.siemens.com/bilddb">http://automation.siemens.com/bilddb</a>
<ul style="list-style-type: none"> <li>• to website: CAX-Download-Manager</li> </ul>	<a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a>
<ul style="list-style-type: none"> <li>• to website: Industry Online Support</li> </ul>	<a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>
<b>last modified:</b>	10/30/2021 