

SIMATIC S7-400, CP 441-1 COMMUNICATIONS MODULE FOR POINT TO POINT CONNECTIONS 1 CHANNEL INCL. CONFIG. PACKAGE ON CD



## General information

Product type designation	CP 441-1
--------------------------	----------

## Supply voltage

Rated value (DC)	
• 5 V DC	Yes
• 24 V DC	Yes

## Input current

from backplane bus 5 V DC, max.	300 mA
---------------------------------	--------

## Power loss

Power loss, typ.	2.1 W; incl. 1x20 mA TTY module
------------------	---------------------------------

## Memory

Memory requirements per interface in memory card of S7-CPU	1 to 5 KB for parameters; 0 to 55 KB for message texts
--	--

## Interfaces

Number of interfaces	1; variable
Interface physics, 20 mA (TTY)	Yes
Interface physics, RS 232C (V.24)	Yes

Interface (physical) RS 422/485 (X.27)	Yes
20 mA (TTY), cable length shielded, max.	1 000 m; At 9600 bps
RS 232, cable length shielded, max.	15 m; At 115200 bps
RS 422/RS 485, cable length shielded, max.	1 200 m; At 19200 bps
<b>Point-to-point</b>	
• Transmission rate, max.	115.2 kbit/s; Min. 300 bps
• supported printers	HP-Deskjet, HP-Laserjet, IBM-Proprinter, user-defined
<b>Integrated protocol driver</b>	
— 3964 (R)	Yes
— ASCII	Yes
— RK512	No
— Printer	Yes
— customer-specific drivers reloadable	No
<b>Transmission rate, 20 mA (TTY)</b>	
— with 3964 (R) protocol, max.	19.2 kbit/s
— with ASCII protocol, max.	19.2 kbit/s
— with printer driver, max.	19.2 kbit/s
<b>Transmission rate, RS 422/485</b>	
— with 3964 (R) protocol, max.	115.2 kbit/s
— with ASCII protocol, max.	115.2 kbit/s
— with printer driver, max.	115.2 kbit/s
<b>Transmission speed, RS 232</b>	
— with 3964 (R) protocol, max.	115.2 kbit/s
— with ASCII protocol, max.	115.2 kbit/s
— with printer driver, max.	115.2 kbit/s
<b>Ambient conditions</b>	
<b>Ambient temperature during operation</b>	
• min.	0 °C
• max.	60 °C
<b>Relative humidity</b>	
• Operation, max.	95 %
<b>Dimensions</b>	
Width	25 mm
Height	290 mm
Depth	210 mm
<b>Weights</b>	
Weight, approx.	580 g; Interface modules: 80 g
<b>last modified:</b>	10/13/2016