

fixed-mounted molded case circuit breaker frame 1600; with RTC and 4AUX trip alarm switch S24; Icu "M" Icu=55kA @ 415V, 3-pole ETU350, LSI, In=800A rotary coding switch Ir=320...800A I<sub>sd</sub>=1...10xIn, I<sub>i</sub>=1.5...15xIn N conductor protec. adjustable opt. w. ext. CT; up to 200% front bus connector offset No communication connection, no measurement function Motorized operating mechanism 24...30 V AC/DC incl. S21 spring energy store signaling switch With electr. and mech. calling Switch-on solenoid (CC) 24 V AC/DC with 2nd auxiliary release UVR, instant Undervoltage 24 V AC/DC with 1st auxiliary release, ST Shunt release 24 V AC/DC T30= Door sealing frame IP30 for fixed-mounted circuit breaker

### Further information

#### Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

#### Industry Mall (Online ordering system)

[https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA2780-1AC06-1BB1-Z\\_T30](https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA2780-1AC06-1BB1-Z_T30)

#### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

[https://support.industry.siemens.com/cs/ww/en/ps/3VA2780-1AC06-1BB1-Z\\_T30](https://support.industry.siemens.com/cs/ww/en/ps/3VA2780-1AC06-1BB1-Z_T30)

#### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3VA2780-1AC06-1BB1-Z\\_T30](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA2780-1AC06-1BB1-Z_T30)

#### CAx-Online-Generator

<http://www.siemens.com/cax>

#### Tender specifications

<http://www.siemens.com/specifications>



last modified:

12/8/2023

