

# Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3282D SIMOTICS XP - 280 M - IM V1 - 8p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

**II 3G Ex ec IIC T3 Gc**  
-/-

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	η <sup>3)</sup>			cosφ <sup>3)</sup>			I <sub>A</sub> /I <sub>N</sub> I <sub>I</sub> /I <sub>N</sub>	M <sub>A</sub> /M <sub>N</sub> T <sub>I</sub> /T <sub>N</sub>	M <sub>K</sub> /M <sub>N</sub> T <sub>B</sub> /T <sub>N</sub>	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4				
<b>DOL duty (S1) - 155(F) to 130(B)</b>																	
400	Δ	50	45.00	-/-	88.00	738	580.0	92.2	92.8	92.6	0.80	0.76	0.67	5.9	2.5	2.5	IE3
690	Y	50	45.00	-/-	51.00	738	580.0	92.2	92.8	92.6	0.80	0.76	0.67	5.9	2.5	2.5	IE3
460	Δ	60	54.00	-/-	90.00	886	580.0	93.0	93.6	93.5	0.81	0.78	0.70	5.9	2.3	2.3	IE2
460	Δ	60	45.00	-/-	77.00	890	485.0	92.4	92.5	91.9	0.79	0.75	0.65	6.8	2.7	2.7	IE3
IM V1 / IM 3011			FS 280 M		IP55		IEC/EN 60034		IEC, DIN, ISO, VDE, EN								
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 34.1 s   47.2 s								

## Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	65 / 79 dB(A) <sup>2) 3)</sup>	66 / 80 dB(A) <sup>2) 3)</sup>	External earthing terminal	With (standard)
Moment of inertia	1.6000 kg m <sup>2</sup>		Vibration severity grade	A
Bearing DE   NDE	6317 C3	6317 C3	Thermal class	F
<b>bearing lifetime</b>			Duty type	S1
L <sub>10mh</sub> , F <sub>Rad</sub> min 50 60Hz for coupling operation	20000 h	16000 h	Direction of rotation	bidirectional
Relubrication interval/quantity DE   NDE	30 g   30 g 8000 h		Frame material	cast iron
Lubricants	Unirex N3		Net weight of the motor (IM B3)	550 kg
Regreasing device	With (standard)		Coating (paint finish)	Standard paint finish C2
Grease nipple	M10x1 DIN 3404 A		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	(B) 3 PTC thermistors - for tripping (2 terminals)
Condensate drainage holes	With (standard)		Method of cooling	IC411 - self ventilated, surface cooled

## Terminal box

Terminal box position	top	Max. cross-sectional area	120 mm <sup>2</sup>
Material of terminal box	cast iron	Cable diameter from ... to ...	34 mm - 45 mm
Type of terminal box	TB1 N01	Cable entry	2xM63x1,5-2xM20x1,5
Contact screw thread	M10		

## Notes:

I<sub>A</sub>/I<sub>N</sub> = locked rotor current / current nominal  
 M<sub>K</sub>/M<sub>N</sub> = locked rotor torque / torque nominal  
 M<sub>K</sub>/M<sub>N</sub> = break down torque / nominal torque  
 1) L<sub>10mh</sub> according to DIN ISO 281 10/2010  
 2) at rated power / at full load  
 3) Value is valid only for DOL operation with motor design IC411

responsible dep. IN LVM	technical reference	created by SPC	approved by	<i>Technical data are subject to change! There may be discrepancies between calculated and rating plate values.</i>	<a href="#">Link documents</a>
	document type datasheet	document status released			document number
	title 1MB1533-2DD23-4GB4-Z H00	rev. 951	creation date 2023-12-14		
© INNOMOTICS 2023					

**Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS**




Motor type : 1CV3282D

SIMOTICS XP - 280 M - IM V1 - 8p

**Special design**

H00 Canopy

**Notes:**

responsible dep. IN LVM	technical reference	created by SPC	approved by	<i>Technical data are subject to change! There may be discrepancies between calculated and rating plate values.</i>	<a href="#">Link documents</a>
<b>SIEMENS</b>	document type datasheet	document status released			
	title 1MB1533-2DD23-4GB4-Z H00	document number			
© INNOMOTICS 2023	rev. 951	creation date 2023-12-14	language en	Page 2/2	