

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3204A

SIMOTICS XP - 200 L - IM B5 - 2p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

II 2D Ex tb IIIC T 120°C Db

-/-

Electrical data

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
400	Δ	50	30.00	-/-	53.00	2955	97.0	93.3	93.6	93.3	0.87	0.83	0.75	7.0	2.5	3.3	IE3
690	Y	50	30.00	-/-	31.00	2955	97.0	93.3	93.6	93.3	0.87	0.83	0.75	7.0	2.5	3.3	IE3
460	Δ	60	33.50	-/-	52.00	3555	90.0	93.0	93.1	92.6	0.87	0.84	0.77	7.1	2.5	3.3	IE3
460	Δ	60	30.00	-/-	47.00	3560	80.0	92.4	92.2	91.4	0.87	0.83	0.74	7.6	2.9	3.6	IE3
IM B5 / IM 3001		FS 200 L		IP65		IEC/EN 60034		IEC, DIN, ISO, VDE, EN									

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 34.3 s | 52.7 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	73 / 80 dB(A) ^{2) 3)}	78 / 86 dB(A) ^{2) 3)}	Vibration severity grade	A
Moment of inertia	0.1340 kg m ²		Thermal class	F
Bearing DE NDE	6212 2Z C3	6212 2Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} , F _{Rad min} 50 60Hz ¹⁾ for coupling operation	40000 h	32000 h	Frame material	cast iron
Regreasing device	Without		Net weight of the motor (IM B3)	225 kg
Grease nipple	-/-		Coating (paint finish)	Standard paint finish C2
Type of bearing	Locating bearing NDE		Color, paint shade	RAL7030
Condensate drainage holes	With (standard)		Motor protection	(B) 3 PTC thermistors - for tripping (2 terminals)
External earthing terminal	With (standard)		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	35 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	27 mm - 35 mm
Type of terminal box	TB1 L01	Cable entry	2xM50x1,5-2xM20x1,5
Contact screw thread	M6		

Notes:

I_A/I_N = locked rotor current / current nominal
 M_A/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque

1) L_{10mh} according to DIN ISO 281 10/2010
 2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	<i>Technical data are subject to change! There may be discrepancies between calculated and rating plate values.</i>	Link documents
IN LVM		SPC			
	document type	document status			
	datasheet	released			
	title	document number			
	1MB1513-2AA43-4FB4				
		rev.	creation date	language	Page
		951	2023-12-14	en	1/1