

SWITCH DISCONNECTOR NEW DESIGN IU=250A, UE=690V, 3-POLE BASIC VERSION WITHOUT 8UC6 HANDLE AND SHAFT WITH TIN-COATED CONTACTS



Figure similar

Model	
product brandname	SETRON
Product designation	Switch Disconnecter 3KA
Design type	For mounting and installation
Insulation voltage / rated value	1 000 V
Protection class	
Protection class IP	IP00
Dissipation	
Power loss [W]	
<ul style="list-style-type: none"> for rated value of the current / at AC / in hot operating state / per pole 	11 W
<ul style="list-style-type: none"> maximum 	33 W
Electricity	
Let-through current / I _{2t} / maximum permissible / in utilization category / AC-22 B / at 400 V	1 000 000 A ² ·s
Main circuit	

Number of poles / for main current circuit	3
Operating power	
<ul style="list-style-type: none"> • at AC-23 A / at 400 V / at 50/60 Hz / rated value • at AC-23 A / at 500 V / at 50/60 Hz / rated value • at AC-23 A / at 690 V / at 50/60 Hz / rated value 	<p>132 000 W</p> <p>132 000 W</p> <p>185 000 W</p>
Operating voltage	
<ul style="list-style-type: none"> • at AC / at 50/60 Hz / rated value • at DC / rated value 	<p>690 V</p> <p>440 V</p>
Rated current I_e / maximum / in utilization category	
<ul style="list-style-type: none"> • AC-21 A / at 400 V • AC-21 A / at 500 V • AC-21 B / at 400 V • AC-21 B / at 500 V • AC-22 A / at 400 V • AC-22 A / at 500 V • AC-22 B / at 400 V • AC-22 B / at 500 V 	<p>250 A</p> <p>250 A</p> <p>250 A</p> <p>250 A</p> <p>250 A</p> <p>250 A</p> <p>250 A</p> <p>250 A</p>

Short circuit

Maximum short-circuit current breaking capacity (I_{cu}) / at 400 V / rated value	120 kA
Conditional rated short-circuit current	
<ul style="list-style-type: none"> • 400V • 500V • in utilization category / AC-21 A / at 400 V • in utilization category / AC-21 A / at 500 V • in utilization category / AC-21 B / at 400 V • in utilization category / AC-21 B / at 500 V • in utilization category / AC-22 A / at 400 V • in utilization category / AC-22 A / at 500 V • in utilization category / AC-22 B / at 400 V • in utilization category / AC-22 B / at 500 V 	<p>100 kA</p> <p>100 kA</p> <p>100 kA</p> <p>100 kA</p> <p>100 kA</p> <p>100 kA</p> <p>100 kA</p> <p>100 kA</p> <p>100 kA</p> <p>100 kA</p>

Connections

Connectable conductor cross-section	
<ul style="list-style-type: none"> • for main contacts <ul style="list-style-type: none"> — stranded / maximum 	150 mm ²
Type of connection, main circuit	Flat-type screw terminal
Type of electrical connection	
<ul style="list-style-type: none"> • for main current circuit 	flat connector

Mechanical Design

Height	160 mm
Width	240 mm

Depth	207 mm
Type of mounting	fixed mounted
Mounting position	any
Mounting type	floor mounting
Mounting type	
<ul style="list-style-type: none"> • front mounting with 4-hole attachment 	No
<ul style="list-style-type: none"> • front mounting with central attachment 	No
<ul style="list-style-type: none"> • rail mounting 	No

Environmental conditions

Ambient temperature

- | | |
|------------------------------|--------|
| • during operation / minimum | -25 °C |
| • during operation / maximum | 55 °C |
| • during storage / minimum | -50 °C |
| • during storage / maximum | 80 °C |

Certificates

Equipment marking

- acc. to DIN EN 61346-2

Q

General Product Approval	Declaration of Conformity	Test Certificates	Shipping Approval	other
--------------------------	---------------------------	-------------------	-------------------	-------



[spezielle Prüfbescheinigung](#)
n



[sonstig](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/3KA5530-1AE01-Z A01>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3KA5530-1AE01-Z A01/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mfb=3KA5530-1AE01-Z A01

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>