

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3317B

SIMOTICS SD - 315 L - IM B3 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Safe Area

-/-

Electrical data

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	η ³⁾			$\cos\phi$ ³⁾			I_A/I_N I_f/I_N	M_A/M_N T_f/T_N	M_K/M_N T_B/T_N	IE-CL	
								4/4	3/4	2/4	4/4	3/4	2/4					
DOL duty (S1) - 155(F) to 130(B)																		
400	Δ	50	315.00	-/-	570.00	1490	2000.0	96.0	96.0	95.6	0.83	0.80	0.70	8.5	3.2	3.5	IE3	
690	Y	50	315.00	-/-	330.00	1490	2000.0	96.0	96.0	95.6	0.83	0.80	0.70	8.5	3.2	3.5	IE3	
460	Δ	60	315.00	-/-	495.00	1792	1680.0	96.2	96.0	95.3	0.83	0.78	0.69	9.4	3.4	3.7	IE3	
460	Δ	60	360.00	-/-	560.00	1790	1920.0	96.2	96.1	95.6	0.84	0.80	0.72	8.3	3.0	3.2	IE3	
IM B3 / IM1001			FS 315 L			IP55		UKCA		IEC/EN 60034			IEC, DIN, ISO, VDE, EN					
Environmental conditions : -20 °C - +40 °C / 1,000 m										Locked rotor time (hot / cold) : 20.7 s 41.4 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	75 / 90 dB(A) ^{2) 3)}	81 / 95 dB(A) ^{2) 3)}	External earthing terminal	(Standard) Yes	
Moment of inertia	5.3900 kg m ²		Vibration severity grade	Grade A	
Bearing DE NDE	6319 C4		6319 C4	Thermal class	F
permissible lateral force on (N)	X_0 : 9300	$X_{0.5}$: 8650	X_{max} : 8000	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional	
L_{10mh} $F_{Rad, min}$ for coupling operation 50 60Hz ¹⁾	40000 h		32000 h	Frame material	cast iron
Relubrication interval/quantity DE NDE	40 g 40 g 6000 h			Net weight of the motor	1560 kg
Lubricants	UNIREX N3			Coating (paint finish)	Standard paint finish C2
Regreasing device	(Standard) Flat type lubricating nipple acc. DIN 3404			Color, paint shade	RAL7030
Grease nipple	M10x1 DIN 3404 A			Motor protection	3 PTC thermistors - for tripping (2 terminals)
Type of bearing	Locating bearing NDE			Method of cooling	IC411 - self ventilated, surface cooled
Condensate drainage holes	(Standard) Yes				

Terminal box

Terminal box position	box at the angle 45°, socket right	Max. cross-sectional area	240 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	42 mm - 54 mm
Type of terminal box	TB3Q61	Cable entry	2xM63x1,5 - 2xM20x1,5
Contact screw thread	6xM12	Cable gland	4 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
 M_A/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque
 1) L_{10mh} according to DIN ISO 281 10/2010
 2) at rated power / at full load
 3) Value is valid only for DOL operation with motor design IC411

responsible dep. IN LVM	technical reference	created by SPC	approved by	<i>Technical data are subject to change! There may be discrepancies between calculated and rating plate values.</i>	Link documents
	document type datasheet	document status released			document number
	title 1LE5503-3AB73-4AB3		rev. 951		
© INNOMOTICS 2023					