

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CE3130B

SIMOTICS XP - 132 S - IM B35 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

II 2G Ex eb IIC T1-T3 Gb

-/-

Electrical data

Tc	U [V]	Δ / Y	f [Hz]	P [kW]	I [A]	n [1/min]	M [Nm]	t _e -time (s)			η ³⁾			cosφ ³⁾			I _A /I _N I _L /I _N	M _A /M _N T _r /T _N	M _K /M _N T _B /T _N	IE-CL
								T1/T2	T3		4/4	3/4	2/4	4/4	3/4	2/4				
T1/ T2	400	Δ	50	5.00	9.80	1470	32.5	0		89.3	90.1	89.8	0.84	0.80	0.71	7.5	2.1	3.0	IE3	
	690	Y	50	5.00	5.70	1470	32.5	0		89.3	90.1	89.8	0.84	0.80	0.71	7.5	2.1	3.0	IE3	
T3	400	Δ	50	5.00	9.80	1470	32.5	27	23	89.3	90.1	89.8	0.84	0.80	0.71	7.5	2.1	3.0	IE3	
	690	Y	50	5.00	5.70	1470	32.5	27	23	89.3	90.1	89.8	0.84	0.80	0.71	7.5	2.1	3.0	IE3	

IM B35 / IM 2001

FS 132 S

IP55

IEC/EN 60034

Environmental conditions : -20 °C - +40 °C / 1,000 m

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	64 / 76 dB(A) ^{2) 3)}	68 / 80 dB(A) ^{2) 3)}	Vibration severity grade	A
Moment of inertia	0.0340 kg m ²		Thermal class	F
Bearing DE NDE	6208 2Z C3	6208 2Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Frame material	cast iron
Regreasing device	Without		Net weight of the motor (IM B3)	67 kg
Grease nipple	-/-		Coating (paint finish)	Standard paint finish C2
Type of bearing	Preloaded bearing DE		Color, paint shade	RAL7030
Condensate drainage holes	With (standard)		Motor protection	(B) 3 PTC thermistors - for tripping (2 terminals)
External earthing terminal	With (standard)		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	6 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	11 mm - 21 mm
Type of terminal box	TB1 H21	Cable entry	2xM32x1,5-2xM16x1,5
Contact screw thread	M4		

Notes:

I_A/I_N = locked rotor current / current nominal
M_A/M_N = locked rotor torque / torque nominal
M_K/M_N = break down torque / nominal torque

1) L_{10mh} according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep. IN LVM	technical reference	created by SPC	approved by	<i>Technical data are subject to change! There may be discrepancies between calculated and rating plate values.</i>	Link documents
	document type datasheet	document status released			document number
	title 1MB1543-1CB03-4JB4	rev. 951	creation date 2023-12-14		
© INNOMOTICS 2023					