

# Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV2072A

SIMOTICS GP - 71 M - IM B14 - 2p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

## Safe Area

-/-

## Electrical data

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	η <sup>3)</sup>			cosφ <sup>3)</sup>			I <sub>A</sub> /I <sub>N</sub> I <sub>I</sub> /I <sub>N</sub>	M <sub>A</sub> /M <sub>N</sub> T <sub>I</sub> /T <sub>N</sub>	M <sub>K</sub> /M <sub>N</sub> T <sub>B</sub> /T <sub>N</sub>	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4				
<b>DOL duty (S1) - 155(F) to 130(B)</b>																	
400	Δ	50	0.37	-/-	0.95	2770	1.3	69.5	70.5	67.9	0.81	0.72	0.59	4.1	2.5	2.5	IE2
690	Y	50	0.37	-/-	0.55	2770	1.3	69.5	70.5	67.9	0.81	0.72	0.59	4.1	2.5	2.5	IE2
460	Δ	60	0.43	-/-	0.93	3370	1.2	72.0	72.5	69.9	0.81	0.73	0.61	4.6	2.5	2.5	IE2
460	Δ	60	0.37	-/-	0.84	3410	1.0	72.0	71.4	67.8	0.77	0.69	0.56	5.1	2.9	3.0	IE2
IM B14 / IM 3601		FS 71 M		IP55		UKCA		IEC/EN 60034		IEC, DIN, ISO, VDE, EN							

Environmental conditions : -20 °C - +40 °C / 1000 m

Locked rotor time (hot / cold) : 31.5 s | 43.1 s

## Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	52 / 63 dB(A) <sup>2) 3)</sup>	57 / 68 dB(A) <sup>2) 3)</sup>	Vibration severity grade	A
Moment of inertia	0.0003 kg m <sup>2</sup>		Thermal class	F
Bearing DE   NDE	6202 2Z C3	6202 2Z C3	Duty type	S1
<b>bearing lifetime</b>			Direction of rotation	bidirectional
L <sub>10mh</sub> , F <sub>Rad min</sub> 50 60Hz <sup>1)</sup> for coupling operation	40000 h	32000 h	Frame material	aluminum
Regreasing device	Without		Net weight of the motor (IM B3)	6 kg
Grease nipple	-/-		Coating (paint finish)	Standard paint finish C2
Type of bearing	Preloaded bearing DE		Color, paint shade	RAL7030
Condensate drainage holes	Without		Motor protection	(A) without (Standard)
External earthing terminal	Without		Method of cooling	IC411 - self ventilated, surface cooled

## Terminal box

Terminal box position	top	Max. cross-sectional area	1.5 mm <sup>2</sup>
Material of terminal box	Aluminium	Cable diameter from ... to ...	9 mm - 17 mm
Type of terminal box	TB1 B00	Cable entry	1xM25x1,5
Contact screw thread	M4	Cable gland	1 plug

## Notes:

I<sub>A</sub>/I<sub>N</sub> = locked rotor current / current nominal  
M<sub>K</sub>/M<sub>N</sub> = locked rotor torque / torque nominal  
M<sub>I</sub>/M<sub>N</sub> = break down torque / nominal torque

1) L<sub>10mh</sub> according to DIN ISO 281 10/2010  
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep. IN LVM	technical reference	created by SPC	approved by	<i>Technical data are subject to change! There may be discrepancies between calculated and rating plate values.</i>	<a href="#">Link documents</a>
	document type datasheet	document status released			document number
	title 1LE1001-0CA23-4KA4	rev. 953	creation date 2024-01-14		
© INNOMOTICS 2024					