



Figure similar

## Data sheet for SIMOTICS S-1FT7

Article No. : 1FT7036-5AK70-1BG2-Z  
Q12

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

### Engineering data

Rated speed	6,000 rpm
Number of poles	6
Rated torque (100 K)	1.7 Nm
Rated current	2.40 A
Static torque (60 K)	2.4 Nm
Static torque (100 K)	3.0 Nm
Stall current (60 K)	3.10 A
Stall current (100 K)	4.00 A
Rotor moment of inertia	1.33 kgcm <sup>2</sup>
Efficiency	90.0 %

### Physical constants

Torque constant	0.76 Nm/A
Voltage constant at 20° C	48.5 V/1000*min <sup>-1</sup>
Winding resistance at 20° C	1.37 Ω
Rotary field inductance	5.9 mH
Electrical time constant	4.30 ms
Mechanical time constant	1.00 ms
Thermal time constant	30 min
Shaft torsional stiffness	4,100 Nm/rad
Net weight of the motor	5.0 kg

### Mechanical data

Motor type	Permanent-magnet synchronous motor
Motor type	Compact
Shaft height	36
Cooling	Natural cooling
Radial runout tolerance	0.035 mm
Concentricity tolerance	0.080 mm
Axial runout tolerance	0.080 mm
Vibration severity grade	Grade A
Degree of protection	IP67
Design acc. to Code I	IM B5 (new flange design)
Temperature monitoring	Pt1000 temperature sensor
Color of the housing	Standard (pearl dark gray similar to RAL 9023)
Shaft end type	Plain shaft
Sensor design	Encoder AS24DQI: Absolut encoder Singleturn 24 bit - with signal connection RJ45
Electrical connection	Connector turnable
Connector size	1

### Optimum operating point

Optimum speed	6,000 rpm
Optimum power	1.1 kW

### Limiting data

Max. permissible speed (mech.)	10,000 rpm
Max. permissible speed (inverter)	10,000 rpm
Maximum torque	12.0 Nm
Maximum current	17.00 A

### Recommended Motor Module

Rated inverter current	5.00 A
Maximum inverter current	15.00 A
Maximum torque	10.8 Nm

### Special design

Q12 Sealing air connection