

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3252B

SIMOTICS SD - 250 M - IM B3 - 4p

| | | |
|------------------|-----------------|-----------|
| Client order no. | Item-No. | Offer no. |
| Order no. | Consignment no. | Project |

Remarks

Safe Area

Electrical data

-/-

| U [V] | Δ / Y | f [Hz] | P [kW] | P [hp] | I [A] | n [1/min] | M [Nm] | $\eta^{3)}$ | | | $\cos\phi^{3)}$ | | | I_A/I_N I_f/I_N | M_A/M_N T_f/T_N | M_K/M_N T_B/T_N | IE-CL |
|---|--------------|-----------|-----------|-----------|----------|--------------|-----------|--------------|------|--|-----------------|------|------|------------------------|------------------------|------------------------|-------|
| | | | | | | | | 4/4 | 3/4 | 2/4 | 4/4 | 3/4 | 2/4 | | | | |
| DOL duty (S1) - 155(F) to 130(B) | | | | | | | | | | | | | | | | | |
| 230 | Δ | 50 | 55.00 | -/- | 168.00 | 1482 | 355.0 | 94.6 | 95.1 | 95.0 | 0.87 | 0.84 | 0.76 | 6.8 | 2.5 | 2.9 | IE3 |
| 400 | Y | 50 | 55.00 | -/- | 96.00 | 1482 | 355.0 | 94.6 | 95.1 | 95.0 | 0.87 | 0.84 | 0.76 | 6.8 | 2.5 | 2.9 | IE3 |
| 460 | Y | 60 | 63.00 | -/- | 97.00 | 1782 | 340.0 | 94.1 | 94.5 | 94.4 | 0.87 | 0.84 | 0.77 | 6.7 | 2.4 | 2.8 | IE2 |
| 460 | Y | 60 | 55.00 | -/- | 84.00 | 1786 | 295.0 | 95.4 | 95.6 | 95.1 | 0.86 | 0.83 | 0.74 | 7.6 | 2.8 | 3.2 | IE3 |
| IM B3 / IM 1001 | | FS 250 M | | IP55 | | UKCA | | IEC/EN 60034 | | IEC, DIN, ISO, VDE, EN | | | | | | | |
| Environmental conditions : -20 °C - +40 °C / 1000 m | | | | | | | | | | Locked rotor time (hot / cold) : 34.9 s 55 s | | | | | | | |

Mechanical data

| | | | | |
|---|--------------------------------|--------------------------------|---------------------------------|---|
| Sound level (SPL / SWL) at 50Hz 60Hz | 66 / 79 dB(A) ^{2) 3)} | 68 / 82 dB(A) ^{2) 3)} | Vibration severity grade | A |
| Moment of inertia | 0.8500 kg m ² | | Thermal class | F |
| Bearing DE NDE | 6215 Z C3 | 6215 Z C3 | Duty type | S1 |
| bearing lifetime | | | Direction of rotation | bidirectional |
| L_{10mh} $F_{Rad, min}$ for coupling operation 50 60Hz ¹⁾ | 40000 h | 32000 h | Frame material | cast iron |
| Regreasing device | Without | | Net weight of the motor (IM B3) | 420 kg |
| Grease nipple | -/- | | Coating (paint finish) | Standard paint finish C2 |
| Type of bearing | Locating bearing NDE | | Color, paint shade | RAL7030 |
| Condensate drainage holes | With (standard) | | Motor protection | (A) without (Standard) |
| External earthing terminal | With (standard) | | Method of cooling | IC411 - self ventilated, surface cooled |

Terminal box

| | | | |
|--------------------------|-----------|--------------------------------|---------------------|
| Terminal box position | top | Max. cross-sectional area | 120 mm ² |
| Material of terminal box | cast iron | Cable diameter from ... to ... | 34 mm - 42 mm |
| Type of terminal box | TB1 N01 | Cable entry | 2xM63x1,5 |
| Contact screw thread | M10 | Cable gland | 2 plugs |

I_A/I_N = locked rotor current / current nominal 1) L_{10mh} according to DIN ISO 281 10/2010 3) Value is valid only for DOL operation with motor design IC411
 M_A/M_N = locked rotor torque / torque nominal 2) at rated power / at full load
 M_K/M_N = break down torque / nominal torque

Transmittal, reproduction, dissemination and/or editing of this document as well as utilization of its contents and communication thereof to others without express authorization are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

| | | | | | |
|----------------------------------|---------------------------------------|--------------------------------------|--------------------------------------|---|--------------------------------|
| Responsible department IN LVM | Technical reference | Created by SPC | Approved by Created automatically | <i>Technical data are subject to change! There may be discrepancies between calculated and rating plate values.</i> | Link documents |
| | Document type Technical data sheet | Document status Released | | | |
| | Title 1LE1503-2CB22-2AA4 | Document number TDS-240321-173748 | | | |
| Restricted © Innomotics 2024 | Rev. AA | Creation date 2024-03-21 | Language en | | |