

fixed-mounted molded case circuit breaker frame 1600; with RTC and 4AUX trip alarm switch S24; Icu "C" Icu=110kA @ 415V, 3-pole ETU350, LSI, In=1000A rotary coding switch Ir=400...1000A I_{sd}=1...10xI_n, I_i=1.5...15xI_n N conductor protec. adjustable opt. w. ext. CT; up to 200% straight bus connector extended No communication connection, no measurement function Manual operating mechanism of the spring energy store With mechanical calling without 2nd auxiliary release without 1st auxiliary release

Model	
product brand name	SENTRON
product designation	Molded case circuit breaker
design of the product	MCCB
design of the actuating element	spring actuator
type of the driving mechanism	without motor drive
type of the driving mechanism / motor drive	No
design of the overcurrent release	ETU350
General technical data	
number of poles	3
size of the circuit-breaker	1600 A
mechanical service life (operating cycles) / typical	10 000
circuit-breaker / Design	3VA2
Voltage	
insulation voltage / rated value	1 000 V
operating voltage / at AC / at 50/60 Hz / rated value	690 V
protection class IP	IP20
<ul style="list-style-type: none"> protection class IP / on the front protection function of the overcurrent release 	IP20 LSI
power loss [W] / for rated value of the current / at AC / in hot operating state / per pole	30 W
Auxiliary circuit	
number of CO contacts / for auxiliary contacts	4
Suitability	
suitability for use	system protection
Adjustable parameters	
adjustable current response value current / of the current-dependent overload release / initial value	400 A
product component <ul style="list-style-type: none"> trip indicator voltage trigger undervoltage release 	Yes No No
product extension / optional / motor drive	Yes
Product function	
product function <ul style="list-style-type: none"> grounding protection 	No
Display and operation	
display version	Without display
Short circuit	
operating short-circuit current breaking capacity (I _{cs}) <ul style="list-style-type: none"> at 415 V / rated value at 500 V / rated value at 690 V / rated value 	110 kA 63 kA 36 kA
maximum short-circuit current breaking capacity (I _{cu}) <ul style="list-style-type: none"> at 415 V / rated value at 440 V / rated value at 500 V / rated value 	110 kA 100 kA 85 kA

• at 690 V / rated value

50 kA

Connections

arrangement of electrical connectors / for main current circuit	Main connection at the front, extension enclosed
type of electrical connection / for main current circuit	busbar connection

Mechanical Design

height	296 mm
width	210 mm
depth	183 mm
fastening method	fixed mounting
net weight	14 kg

Environmental conditions

ambient temperature / during operation	
• minimum	-25 °C
• maximum	70 °C
ambient temperature / during storage	
• minimum	-40 °C
• maximum	70 °C

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA2710-3AC05-0AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3VA2710-3AC05-0AA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA2710-3AC05-0AA0

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

last modified:

2/19/2024 