

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CD3133C

SIMOTICS XP - 132 M - IM B5 - 6p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks **II 2G Ex db eb IIC T4 Gb**

Electrical data

-/-

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
230	Δ	50	4.78	-/-	20.00	975	46.8	88.2	87.9	86.0	0.68	0.59	0.44	7.8	3.1	3.9	IE3
400	Y	50	4.78	-/-	11.50	975	46.8	88.2	87.9	86.0	0.68	0.59	0.44	7.8	3.1	3.9	IE3
460	Y	60	4.78	-/-	10.20	1180	38.7	90.9	90.2	87.5	0.65	0.56	0.41	9.0	3.5	4.6	IE3
IM B5 / IM 3001		FS 132 M			IP55		IEC/EN 60034										

Environmental conditions : -20 °C - +55 °C / 1000 m

Locked rotor time (hot / cold) : 19.9 s | 27 s

These values are calculated. The final rating plate data will be calculated when the order is placed

The efficiency values and efficiency class according to EuP directive are valid for standard power ratings under standard conditions.

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	58 / 66 dB(A) ^{2) 3)}	69 / 77 dB(A) ^{2) 3)}	Thermal class	F
Moment of inertia	0.0519 kg m ²		Duty type	S1
Bearing DE NDE	6308 2Z C3	6308 2Z C3	Direction of rotation	bidirectional
bearing lifetime			Frame material	cast iron
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Net weight of the motor	114 kg
Regreasing device	Without		Motor weight incl. options	114 kg
Grease nipple	-/-		Coating (paint finish)	Standard paint finish C2
Type of bearing	Locating bearing DE		Color, paint shade	RAL7030
Condensate drainage holes	Without		Motor protection	(B) 3 PTC thermistors - for tripping (2 terminals)
External earthing terminal	With (standard)		Method of cooling	IC411 - self ventilated, surface cooled
Vibration severity grade	A			

Terminal box

Terminal box position	top	Max. cross-sectional area	6 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	11 mm - 21 mm
Type of terminal box	TB1 H21	Cable entry	-/-
Contact screw thread	M4		

I_A/I_N = locked rotor current / current nominal
 M_A/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque
 1) L_{10mh} according to DIN ISO 281 10/2010
 2) at rated power / at full load
 3) Value is valid only for DOL operation with motor design IC411

Transmittal, reproduction, dissemination and/or editing of this document as well as utilization of its contents and communication thereof to others without express authorization are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

Responsible department IN LVM	Technical reference	Created by SPC	Approved by Created automatically	<i>Technical data are subject to change! There may be discrepancies between calculated and rating plate values.</i>	Link documents
	Document type Technical data sheet	Document status Released			
	Document title 1MB1553-1CC32-2FB4-Z	Document number TDS-240507-152710			
Restricted © Innomotics 2024	B44+H70+N07	Revision AA	Creation date 2024-05-07		

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CD3133C

SIMOTICS XP - 132 M - IM B5 - 6p

Special design

B44	Version for converter operation with voltage source converter with operation data utilisation thermal class F	N07	Temperature class 155 (F), utilised to 130 (B), cooling medium temperature 55°C, power reduced
H70	Second outer earthing		

Transmittal, reproduction, dissemination and/or editing of this document as well as utilization of its contents and communication thereof to others without express authorization are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

Responsible department IN LVM	Technical reference	Created by SPC	Approved by Created automatically	<i>Technical data are subject to change! There may be discrepancies between calculated and rating plate values.</i>	Link documents
	Document type Technical data sheet	Document status Released			
	Document title 1MB1553-1CC32-2FB4-Z	Document number TDS-240507-152710			
Restricted © Innomatics 2024	B44+H70+N07	Revision AA	Creation date 2024-05-07		