

SD motor type: 1CV3205B low-voltage motor, IEC squirrel-cage rotor, self-cooled, IP55 temperature class 155(F) according to 130(B) gray cast iron housing Performance Line Premium Efficiency IE3, 60 Hz, P60: IE2 4-pole * size 200L, * 30 kW (50 Hz) 34.5 kW (60 Hz) standard color RAL 7030 if no order code is specified for selecting another color. The product will be delivered with either the Siemens or Innomotics product brand. 3 AC 60 Hz 460 VD * 60 Hz power IM B 3, 3 PTC thermistors for disconnection (2 terminals) Terminal box at top B02=Acceptance test certificate 3.1 according to EN 10204 H20=Degree of protection IP65 N06=Temperature class 155 (F), utilized according to 130(B), Coolant temperature 50°, derating approx. 8% Q02=Anti-condensation heating for 230 V (2 terminals) Y56=Paint finish in other RAL colors (for selection see catalog) RAL... Y80=Additional rating plate with deviating rating plate data

Further information

Industry Online Support (Manuals, Catalogs, Certificates, FAQ, ...)

<https://support.industry.siemens.com/cs/products?mfn=ps&lc=en-WW>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com>

