



Figure similar

Data sheet for SIMOTICS M-1PH8

Article No. : **1PH8226-2DF12-2AC1-Z**
X06

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

		P _N [kW]	M _N [Nm]	I _N [A]	U _N [V]	f _N [Hz]	n _N [rpm]	M _{max} [Nm]	I _{max} [A]	n _{max} [rpm]	M ₀ [Nm]	I ₀ [A]	η	cos φ	I _μ [A]
Y	ALM 400V	156.0	851.0	295.0	335	117.0	1,750	3,200	1,120.0	3,500	944.0	320	0.966	0.000	0.0
	BLM/SLM 400V	134.0	853.0	295.0	288	100.0	1,500	3,200	1,120.0	3,500	944.0	320	0.967	0.000	0.0
	ALM/BLM/SLM 480V	157.0	750.0	260.0	378	133.0	2,000	3,200	1,120.0	3,500	944.0	320	0.964	0.000	0.0

Mechanical data

Motor type	Permanent-magnet synchronous motor
Shaft height	225
Cooling	Forced ventilation NDE -> DE
Vibration severity grade	A
Shaft and flange accuracy	N
Degree of protection	IP55
Design acc. to Code I	IM B5 with A550 flange (IM V3)
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Light ivory RAL 1015
Type of the bearing	Standard
Shaft end	Feather key with half key balancing
Encoder system	Incremental encoder 22 bit with commutation position 11 bit, max. encoder speed = 12000 rpm

Physical constants

Thermal time constant	26 min
Moment of inertia	16,600 kgcm ²
Weight (approx.)	700 kg

Connection

Type of electrical connection	Terminal box
Position of the connection	NDE top
Power connection	NDE
Signal connection	right
Terminal box designation	1XB7700-P02

Cooling data and sound pressure level

Airflow, min.	0.31 m ³ /s
Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB	73 dB ¹⁾
Air discharge	axial
Pressure drop	650 Pa

External fan

Max. power consumption

1 AC 200 ... 277 V (±10%) 50/60 Hz ±10% 2.0 ... 2.3 A

Special design

X06 Paint finish: Pale ivory RAL 1015

¹⁾ at a rated frequency of 2 kHz and a speed range of up to 3500 rpm