

SD motor type: 1CV3226B low-voltage motor, IEC squirrel-cage rotor, self-cooled, IP55 temperature class 155(F) according to 130(B) gray cast iron housing, increased power Basic Line Premium Efficiency IE3, 60 Hz, P60: IE2 4-pole \* size 225M \* 55 kW (50 Hz) 63 kW (60 Hz) standard color RAL 7030 if no order code is specified for selecting another color. The product will be delivered with either the Siemens or Innomotics product brand. 3 AC 50 Hz 400 VD/690 VY \* 3 AC 60 Hz 460 VD IM V 1 without canopy, flange: FF400 (A450) 3 PTC thermistors for disconnection (2 terminals) Terminal box at top D03=Coolant temperature -40 to +40 °C D47=TR CU product safety certificate EAC for Eurasian customs union F01=built-on holding brake F11=Brake control voltage 230 V AC, 50/60 Hz F50=Mechanical-manual release of brake with actuating lever F70=Mounting of external fan H00=Canopy L51=Bearing insulation NDE Q02=Anti-condensation heating for 230 V (2 terminals) R62=Auxiliary terminal box cast iron (small) S02=Special paint finish

#### Further information

Industry Online Support (Manuals, Catalogs, Certificates, FAQ, ...)

<https://support.industry.siemens.com/cs/products?mfn=ps&lc=en-WW>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com>

