

SD motor type: 1CV3162C low-voltage motor, IEC squirrel-cage rotor, self-cooled, IP55 temperature class 155(F) according to 130(B) gray cast iron housing Basic Line Premium Efficiency IE3, 6-pole \* size 160M, \* 7.5 kW (50 Hz) standard color RAL 7030 if no order code is specified for selecting another color. The product will be delivered with either the Siemens or Innomotics product brand. Non-standard winding 3 AC..Hz,..V,..kW IM B 5, flange: FF300 (A350) 1 Pt1000 resistance thermometer (2 terminals) Terminal box on left-hand side B02=Acceptance test certificate 3.1 according to EN 10204 F01=built-on holding brake F11=Brake control voltage 230 V AC, 50/60 Hz F50=Mechanical-manual release of brake with actuating lever F70=Mounting of external fan G04=Mounting of rotary pulse encoder LL 861 900 220, 1024 l (Leine & Linde) 1024 pulses per revolution Mounting costs with device R62=Auxiliary terminal box cast iron (small)

## Further information

Industry Online Support (Manuals, Catalogs, Certificates, FAQ, ...)

<https://support.industry.siemens.com/cs/products?mfn=ps&lc=en-WW>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com>

