



Figure similar

Data sheet for SIMOTICS M-1PH8

Article No. : **1PH8224-1MF00-2DB2-Z**
L00+P00

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

		P _N [kW]	M _N [Nm]	I _N [A]	U _N [V]	f _N [Hz]	n _N [rpm]	M _{max} [Nm]	I _{max} [A]	n _{max} [rpm]	M ₀ [Nm]	I ₀ [A]	η	cos φ	I _μ [A]
Y	ALM 400V	110.0	600.0	198.0	395	58.9	1,750	1,550	485.0	4,500	600.0	198	0.956	0.850	87.0
	BLM/SLM 400V	95.0	605.0	200.0	340	50.5	1,500	1,550	485.0	4,500	605.0	200	0.953	0.850	87.0
	ALM/BLM/SLM 480V	124.0	592.0	196.0	460	67.2	2,000	1,550	485.0	4,500	592.0	196	0.957	0.830	90.0

Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	225
Cooling	Forced ventilation DE -> NDE
Vibration severity grade	SR/A
Shaft and flange accuracy	R
Degree of protection	IP55
Design acc. to Code I	IM B3 (IM B6, IM B7, IM B8, IM V6)
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Standard
Shaft end	Feather key with half key balancing
Encoder system	Incremental encoder sin/cos 1Vpp 2048 S/R with C- and D-Spur, max. encoder speed = 12000 rpm

Physical constants

Thermal time constant	49 min
Moment of inertia	14,800 kgcm ²
Weight (approx.)	610 kg

Connection

Type of electrical connection	Terminal box
Position of the connection	NDE top
Power connection	left
Signal connection	DE
Terminal box designation	1XB7422-P06

Cooling data and sound pressure level

Airflow, min.	0.31 m ³ /s
Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB	73 dB ¹⁾
Air discharge	axial
Pressure drop	650 Pa

External fan

Max. power consumption

1 AC 200 ... 277 V (±10%) 50/60 Hz ±10% 2.0 ... 2.3 A

Special design

- L00 Terminal box replaced by the next larger terminal box
- P00 Undrilled cable entry plate

¹⁾ at a rated frequency of 2 kHz and a speed range of up to 3500 rpm