

SD motor type: 1CV3252B low-voltage motor, IEC squirrel-cage rotor, self-cooled, IP55 temperature class 155(F) according to 130(B) gray cast iron housing Basic Line Premium Efficiency IE3, 60 Hz, P60: IE2 4-pole * size 250M * 55 kW (50 Hz) 63 kW (60 Hz) standard color RAL 7030 if no order code is specified for selecting another color. The product will be delivered with either the Siemens or Innomotics product brand. 3 AC 50 Hz 400 VD/690 VY * 3 AC 60 Hz 460 VD IM V 1 without canopy, flange: FF500 (A550) 3 PTC thermistors for disconnection (2 terminals) Terminal box at top B02=Acceptance test certificate 3.1 according to EN 10204 B07=extra rating plate voltage tolerance B12=Seaworthy packaging for non-overseas customers D04=Coolant temperature -30 to +40 °C F74=Sheet metal fan cover F76=With external metal fan H00=Canopy H07=Stainless screws (external) H20=Degree of protection IP65 Q02=Anti-condensation heating for 230 V (2 terminals) Q80=Extension of the liability for defects by 12 to a total of 24 months as of delivery R18=Cable gland in metal max. Assembly S03=Special paint finish, sea air resistant

Further information

Industry Online Support (Manuals, Catalogs, Certificates, FAQ, ...)

<https://support.industry.siemens.com/cs/products?mf=ps&lc=en-WW>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com>

