

Data sheet for three-phase Squirrel-Cage-Motors INNOMOTICS



Motor type : 1AV3112B

INNOMOTICS GP - 112 M - IM B5 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Safe Area

Electrical data

-/-

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	η ³⁾			$\cos\phi$ ³⁾			I_A/I_N I_f/I_N	M_A/M_N T_f/T_N	M_K/M_N T_B/T_N	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4				
DOL duty (S1) - 155(F) to 130(B)																	
220	Δ	60	4.55	-/-	16.10	1760	24.5	89.5	90.0	89.3	0.83	0.78	0.67	7.3	2.5	3.8	IE3
380	Y	60	4.55	-/-	9.30	1760	24.5	89.5	90.0	89.3	0.83	0.78	0.67	7.3	2.5	3.8	IE3
220	Δ	60	3.70	-/-	13.60	1770	20.0	89.5	90.0	88.3	0.80	0.72	0.60	8.2	2.9	4.3	IE3
380	Y	60	3.70	-/-	7.90	1770	20.0	89.5	90.0	88.3	0.80	0.72	0.60	8.2	2.9	4.3	IE3
IM B5 / IM 3001		FS 112 M		IP55		UKCA		IEC/EN 60034		IEC, DIN, ISO, VDE, EN				KS C IEC60034-2-1			
Environmental conditions : -20 °C - +40 °C / 1000 m										Locked rotor time (hot / cold) : 16.1 s 21.8 s							

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	58 / 70 dB(A) ^{2) 3)}	62 / 74 dB(A) ^{2) 3)}	Vibration severity grade	A
Moment of inertia	0.0170 kg m ²		Thermal class	F
Bearing DE NDE	6206 2Z C3	6206 2Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L_{10mh} $F_{Rad, min}$ for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Frame material	aluminum
Regreasing device	Without		Net weight of the motor (IM B3)	34 kg
Grease nipple	-/-		Coating (paint finish)	Standard paint finish C2
Type of bearing	Preloaded bearing DE		Color, paint shade	RAL7030
Condensate drainage holes	Without		Motor protection	(A) without (Standard)
External earthing terminal	Without		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	4 mm ²
Material of terminal box	Aluminium	Cable diameter from ... to ...	11 mm - 21 mm
Type of terminal box	TB1 F00	Cable entry	2xM32x1,5
Contact screw thread	M4	Cable gland	2 plugs

I_A/I_N = locked rotor current / current nominal
 M_A/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque
 1) L_{10mh} according to DIN ISO 281 10/2010
 2) at rated power / at full load
 3) Value is valid only for DOL operation with motor design IC411

Transmittal, reproduction, dissemination and/or editing of this document as well as utilization of its contents and communication thereof to others without express authorization are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

Responsible department IN LVM	Technical reference	Created by SPC	Approved by Created automatically	<i>Technical data are subject to change! There may be discrepancies between calculated and rating plate values.</i>	Link documents
INNOMOTICS	Document type Technical data sheet	Document status Released			
	Document title 1LE1043-1BB21-7FA4-Z	Document number TDS-240927-111149			
Restricted © Innomotics 2024	D22+D33	Revision AA	Creation date 2024-09-27		Language en

Data sheet for three-phase Squirrel-Cage-Motors INNOMOTICS



Motor type : 1AV3112B

INNOMOTICS GP - 112 M - IM B5 - 4p

Special design

D22	Motor without CE character for export outside the EEA (see EU regulation 2019/1781)	D33	KEA Korea Energy Efficiency Label
-----	---	-----	-----------------------------------

Transmittal, reproduction, dissemination and/or editing of this document as well as utilization of its contents and communication thereof to others without express authorization are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

Responsible department IN LVM	Technical reference	Created by SPC	Approved by Created automatically	<i>Technical data are subject to change! There may be discrepancies between calculated and rating plate values.</i>	Link documents
INNOMOTICS	Document type Technical data sheet	Document status Released			
	Document title 1LE1043-1BB21-7FA4-Z	Document number TDS-240927-111149			
Restricted © Innomotics 2024	D22+D33	Revision AA	Creation date 2024-09-27		