SIEMENS

Data sheet

6AV7886-0DB21-3AA0

SIMATIC IPC277G (nanopanel PC); 15" multi-touch (1920 x 1080); 3x 10/100/1000 Mbps Ethernet RJ45; 2x display port graphic; 4x USB 3.1, 2x M.2 extension slot; 24 V DC industrial power supply Atom X6413E (4-core); 8 GB RAM; without COM; 240 GB SSD; without hardware extension; without software; ;

| General information | |
|--|----------------------------|
| Product type designation | IPC277G |
| Display | |
| Design of display | 15" TFT multi-touch |
| Screen diagonal | 15 in |
| Resolution (pixels) | |
| Horizontal image resolution | 1 920 pixel |
| Vertical image resolution | 1 080 pixel |
| Backlighting | |
| MTBF backlighting (at 25 °C) | 50 000 h |
| Control elements | |
| Touch operation | |
| Design as multi-touch screen | Yes; Projective-capacitive |
| Installation type/mounting | |
| central design | Yes |
| Mounting in portrait format possible | Yes |
| Power loss | |
| In full configuration | 80 W |
| Dimensions | |
| Width of the housing front | 398 mm |
| Height of housing front | 257 mm |
| Mounting cutout, width | 382 mm |
| Mounting cutout, height | 241 mm |
| Overall depth | 105 mm |
| Weights | |
| Weight, approx. | 5.3 kg |

last modified:

10/11/2024 🖸