

# Data sheet for three-phase Squirrel-Cage-Motors INNOMOTICS



Motor type : 1CV3222A

INNOMOTICS SD - 225 M - IM B3 - 2p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Safe Area

## Electrical data

-/-

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	η <sup>3)</sup>			cosφ <sup>3)</sup>			I <sub>A</sub> /I <sub>N</sub> I <sub>I</sub> /I <sub>N</sub>	M <sub>A</sub> /M <sub>N</sub> T <sub>I</sub> /T <sub>N</sub>	M <sub>K</sub> /M <sub>N</sub> T <sub>B</sub> /T <sub>N</sub>	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4				
<b>DOL duty (S1) - 155(F) to 130(B)</b>																	
380	Δ	50	45.00	-/-	82.00	2960	145.0	94.0	94.5	94.4	0.89	0.87	0.80	6.9	2.4	3.1	IE3
660	Y	50	45.00	-/-	47.00	2960	145.0	94.0	94.5	94.4	0.89	0.87	0.80	6.9	2.4	3.1	IE3
440	Δ	60	51.00	-/-	80.00	3560	137.0	93.6	93.9	93.6	0.89	0.87	0.81	6.8	2.4	3.0	IE3
440	Δ	60	45.00	-/-	72.00	3570	120.0	93.6	93.7	93.1	0.88	0.85	0.78	7.6	2.7	3.3	IE3
IM B3 / IM 1001		FS 225 M		IP55		UKCA		IEC/EN 60034		IEC, DIN, ISO, VDE, EN							
Environmental conditions : -20 °C - +40 °C / 1000 m										Locked rotor time (hot / cold) : 19.3 s   33.3 s							

## Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	73 / 87 dB(A) <sup>2) 3)</sup>	75 / 89 dB(A) <sup>2) 3)</sup>	Vibration severity grade	A
Moment of inertia	0.2600 kg m <sup>2</sup>		Thermal class	F
Bearing DE   NDE	6213 Z C3	6213 Z C3	Duty type	S1
<b>bearing lifetime</b>			Direction of rotation	bidirectional
L <sub>10mh</sub> F <sub>Rad min</sub> for coupling operation 50 60Hz <sup>1)</sup>	40000 h	32000 h	Frame material	cast iron
Regreasing device	Without		Net weight of the motor (IM B3)	315 kg
Grease nipple	-/-		Coating (paint finish)	Standard paint finish C2
Type of bearing	Locating bearing NDE		Color, paint shade	RAL7030
Condensate drainage holes	With (standard)		Motor protection	(B) 3 PTC thermistors - for tripping (2 terminals)
External earthing terminal	With (standard)		Method of cooling	IC411 - self ventilated, surface cooled

## Terminal box

Terminal box position	top	Max. cross-sectional area	35 mm <sup>2</sup>
Material of terminal box	cast iron	Cable diameter from ... to ...	27 mm - 35 mm
Type of terminal box	TB1 L01	Cable entry	2xM50x1,5-2xM20x1,5
Contact screw thread	M8	Cable gland	4 plugs

I<sub>A</sub>/I<sub>N</sub> = locked rotor current / current nominal  
 M<sub>A</sub>/M<sub>N</sub> = locked rotor torque / torque nominal  
 M<sub>K</sub>/M<sub>N</sub> = break down torque / nominal torque  
 1) L<sub>10mh</sub> according to DIN ISO 281 10/2010  
 2) at rated power / at full load  
 3) Value is valid only for DOL operation with motor design IC411

Transmittal, reproduction, dissemination and/or editing of this document as well as utilization of its contents and communication thereof to others without express authorization are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

Responsible department IN LVM	Technical reference	Created by SPC	Approved by Created automatically	<i>Technical data are subject to change! There may be discrepancies between calculated and rating plate values.</i>	<a href="#">Link documents</a>
<b>INNOMOTICS</b>	Document type Technical data sheet	Document status Released			
	Document title 1LE1503-2BA23-3AB4-Z	Document number TDS-241015-124306			
Restricted © Innomotics 2024	D47	Revision AA	Creation date 2024-10-15	Language en	Page 1/2

**Data sheet for three-phase Squirrel-Cage-Motors INNOMOTICS**




Motor type : 1CV3222A

INNOMOTICS SD - 225 M - IM B3 - 2p

**Special design**

D47 TR CU product safety certificate EAC for the Eurasian Customs Union

Transmittal, reproduction, dissemination and/or editing of this document as well as utilization of its contents and communication thereof to others without express authorization are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

Responsible department IN LVM	Technical reference	Created by SPC	Approved by Created automatically	<i>Technical data are subject to change! There may be discrepancies between calculated and rating plate values.</i>	<a href="#">Link documents</a>
<b>INNOMOTICS</b>	Document type Technical data sheet	Document status Released			
	Document title 1LE1503-2BA23-3AB4-Z	Document number TDS-241015-124306			
Restricted © Innomotics 2024	D47	Revision AA	Creation date 2024-10-15		